

রেজিস্টার্ড নং ডি এ-১

বাংলাদেশ



গেজেট

অতিরিক্ত সংখ্যা
কর্তৃপক্ষ কর্তৃক প্রকাশিত

সোমবার, এপ্রিল ৮, ২০২৪

[বেসরকারি ব্যক্তি এবং কর্পোরেশন কর্তৃক অর্থের বিনিময়ে জারীকৃত বিজ্ঞাপন ও নোটিশসমূহ।]

Civil Aviation Authority of Bangladesh

Gazette

Dhaka, ১৬ ফাল্গুন, ১৪৩০/ 29 February, 2024

No. CAAB 30.31.0000.111.37.001.21—In exercise of the power conferred by Section 47, read with Section 14 of the Civil Aviation Act, 2017 (Act No. 18 of 2017), hereinafter referred as the "Act", the Chairman of the Civil Aviation Authority of Bangladesh is pleased to issue the following Air Navigation Order ANO Part-145 "Approved Maintenance Organization".

2. It shall come into force from the date of gazette publication.

Air Vice Marshal M Mafidur Rahman

BBP, BSP, BUP, ndu, afwc, psc

Chairman

Civil Aviation Authority of Bangladesh.

(৬৩১৯)

মূল্য : টাকা ১১০.০০

APPROVED MAINTENANCE ORGANISATION

Civil Aviation Authority of Bangladesh, in exercise of the powers conferred on it under Section 14 of the Civil Aviation Act 2017 has adopted this Regulation.

This Regulation shall be cited as ANO Part-145 Approved Maintenance Organization and shall come in to force immediately.

Guidance Material, GM Part-145 is a separate document which provides guidance for the compliance of airworthiness requirement of this ANO. Section numbering of the GM part-145 is synchronized with that of this ANO.

145.A.1 General

For the purpose of these orders, mandatory clauses are denoted by use of the words "shall" or "must", whereas the words "may" or "should" are used for permissive or recommended clauses.

For the purpose of this Part, Part-M for organisations approved by the Civil Aviation Authority of Bangladesh shall be ANO Part-M.

For the purpose of this Part, Part-21 for organisations approved by the Civil Aviation Authority of Bangladesh shall be ANO Part-21.

For the purpose of this Part, Part-66 for organisations approved by the Civil Aviation Authority of Bangladesh shall be ANO Part-66.

For the purpose of this Part, Part-147 for organisations approved by the Civil Aviation Authority of Bangladesh shall be ANO Part-147.

Within the scope of this regulation, the following definitions shall apply:

- (a) 'Aircraft' means any machine that can derive support in the atmosphere from the reactions of the air other than reactions of the air against the earth's surface;
- (b) 'Certifying staff' means personnel responsible for the release of an aircraft or a component after maintenance;
- (c) 'large aircraft' means an aircraft, classified as an aeroplane with a maximum take-off mass of more than 5,700 kg, or a multi-engine helicopter;

- (d) ‘large aeroplane’ means an aeroplane of more than 5700 kg (12500 pounds) maximum certificated take-off weight. The category ‘Large Aeroplane’ does not include the commuter aeroplane category
- (e) “Commuter category aeroplane” means a propeller-driven twin-engined aeroplane that has a seating configuration, excluding the pilot seat(s) of nineteen or fewer and a maximum certified takeoff weight of 8618 kg (19000 lb).
- (f) ‘Maintenance’ means any one or combination of overhaul, repair, inspection, replacement, modification or defect rectification of an aircraft or component, with the exception of pre-flight inspection;
- (g) ‘Organisation’ means a natural person, a legal person or part of a legal person. Such an organisation may hold more than one Part 145 approval;
- (h) ‘Pre-flight inspection’ means the inspection carried out before flight to ensure that the aircraft is fit for the intended flight;
- (i) “Principle place of business” means the head office or the registered office of the undertaking within which the principle financial functions and operational control of the activities referred to in this Regulation are exercised.
- (j) “Complex Motor Power Aircraft” or CMPA means:
- i. An aeroplane:
 - with a maximum certificated take-off mass exceeding 5 700 kg, or
 - certificated for a maximum passenger seating configuration of more than nineteen, or
 - certificated for operation with a minimum crew of at least two pilots, or
 - equipped with (a) turbojet engine(s) or more than one turboprop engine, or
 - ii. A helicopter certificated:
 - for a maximum take-off mass exceeding 3 175 kg, or
 - for a maximum passenger seating configuration of more than nine, or
 - for operation with a minimum crew of at least two pilots, or
 - iii. A tilt rotor aircraft;

- (k) "Critical maintenance task" means: a maintenance task that involves the assembly or any disturbance of a system or any part of an aircraft, engine or propeller that if an error occurred during its performance, could directly endanger the flight safety.

145.A.5 Applicability

Organisations involved in the maintenance of large aircraft or of aircraft used for commercial air transport and components intended for fitment thereto, shall be approved in accordance with the provisions of this Part.

145.A.10 Scope

This Section establishes the requirements to be met by an organisation to qualify for the issue or continuation of an approval for the maintenance of aircraft and components.

AMC 145.A.10 Scope

1. Line Maintenance should be understood as any maintenance that is carried out before flight to ensure that the aircraft is fit for the intended flight.
 - (a) Line Maintenance may include:
 - Trouble shooting.
 - Defect rectification.
 - Component replacement with use of external test equipment if required. Component replacement may include components such as engines and propellers.
 - Scheduled maintenance and/or checks including visual inspections that will detect obvious unsatisfactory conditions/discrepancies but do not require extensive in depth inspection. It may also include internal structure, systems and powerplant items which are visible through quick opening access panels/doors.
 - Minor repairs and modifications which do not require extensive disassembly and can be accomplished by simple means.
 - (b) For temporary or occasional cases (ADs, SBs) the Quality Manager may accept base maintenance tasks to be performed by a line maintenance organisation provided all requirements are fulfilled as defined by the CAAB.

- (c) Maintenance tasks falling outside these criteria are considered to be Base Maintenance.
- (d) Aircraft maintained in accordance with ‘progressive’ type programmes should be individually assessed in relation to this paragraph. In principle, the decision to allow some ‘progressive’ checks to be carried out should be determined by the assessment that all tasks within the particular check can be carried out safely to the required standards at the designated line maintenance station.
2. Where the organisation uses facilities both inside and outside Bangladesh such as satellite facilities, sub-contractors, line stations etc., such facilities may be included in the approval without being identified on the approval certificate subject to the maintenance organisation exposition identifying the facilities and containing procedures to control such facilities and the CAAB being satisfied that they form an integral part of the approved maintenance organisation.

145.A.15 Application

An application for the issue or change of an approval shall be made to the CAAB in a form and manner established by CAAB.

AMC 145.A.15 Application

In a form and in a manner established by the CAAB means that the application should be made on a CAAB Form 2 (refer to Appendix III to AMC to Part-145).

145.A.20 Terms of Approval

The organisation shall specify the scope of work deemed to constitute approval in its exposition (Appendix II of regulations contains a table of all classes and ratings).

AMC 145.A.20 Terms of approval

The following table identifies the ATA Specification 2200 chapter for the category C component rating. If the maintenance manual (or equivalent document) does not follow the ATA Chapters, the corresponding subjects still apply to the applicable C rating.

CLASS	RATING	ATA CHAPTERS
COMPONENTS OTHER THAN COMPLETE ENGINES OR APUs	C1 Air Cond & Press	21
	C2 Auto Flight	22
	C3 Comms and Nav	23, 34
	C4 Doors - Hatches	52
	C5 Electrical Power & Lights	24, 33, 85
	C6 Equipment	25, 38, 44, 45, 50
	C7 Engine – APU	49, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83;
	C8 Flight Controls	27, 55, 57.40, 57.50, 57.60, 57.70
	C9 Fuel	28, 47
	C10 Helicopters - Rotors	62, 64, 66, 67
	C11 Helicopter - Trans	63, 65
	C12 Hydraulic Power	29
	C13 Indicating/Recording Systems	31, 42, 46
	C14 Landing Gear	32
	C15 Oxygen	35
	C16 Propellers	61
	C17 Pneumatic & Vacuum	36, 37
	C18 Protection ice/rain/fire	26, 30
	C19 Windows	56
	C20 Structural	53, 54, 57.10, 57.20, 57.30
	C21 Water Ballast	41
	C22 Propulsion Augmentation	84

145.A.25 Facility Requirements

The organisation shall ensure that:

- (a) Facilities are provided appropriate for all planned work, ensuring in particular, protection from the weather elements. Specialised workshops and bays are segregated as appropriate, to ensure that environmental and work area contamination is unlikely to occur.
 1. For base maintenance of aircraft, aircraft hangars are both available and large enough to accommodate aircraft on planned base maintenance;
 2. For component maintenance, component workshops are large enough to accommodate the components on planned maintenance.
- (b) Office accommodation is provided for the management of the planned work referred to in paragraph (a), and certifying staff so that they can carry out their designated tasks in a manner that contributes to good aircraft maintenance standards.
- (c) The working environment including aircraft hangars, component workshops and office accommodation is appropriate for the task carried out and in particular special requirements observed. Unless otherwise dictated by the particular task environment, the working environment must be such that the effectiveness of personnel is not impaired:
 1. temperatures must be maintained such that personnel can carry out required tasks without undue discomfort.
 2. dust and any other airborne contamination are kept to a minimum and not be permitted to reach a level in the work task area where visible aircraft/component surface contamination is evident. Where dust/other airborne contamination results in visible surface contamination, all susceptible systems are sealed until acceptable conditions are re-established.
 3. lighting is such as to ensure each inspection and maintenance task can be carried out in an effective manner.
 4. noise shall not distract personnel from carrying out inspection tasks. Where it is impractical to control the noise source, such personnel are provided with the necessary personal equipment to stop excessive noise causing distraction during inspection tasks.

5. where a particular maintenance task requires the application of specific environmental conditions different to the foregoing, then such conditions are observed. Specific conditions are identified in the maintenance data.
 6. the working environment for line maintenance is such that the particular maintenance or inspection task can be carried out without undue distraction. Therefore where the working environment deteriorates to an unacceptable level in respect of temperature, moisture, hail, ice, snow, wind, light, dust/other airborne contamination, the particular maintenance or inspection tasks must be suspended until satisfactory conditions are re-established.
- (d) Secure storage facilities are provided for components, equipment, tools and material. Storage conditions ensure segregation of serviceable components and material from unserviceable aircraft components, material, equipment and tools. The conditions of storage are in accordance with the manufacturer's instructions to prevent deterioration and damage of stored items. Access to storage facilities is restricted to authorised personnel.

AMC 145.A.25(a) Facility requirements

1. Where the hangar is not owned by the organisation, it may be necessary to establish proof of tenancy. In addition, sufficiency of hangar space to carry out planned base maintenance should be demonstrated by the preparation of a projected aircraft hangar visit plan relative to the maintenance programme. The aircraft hangar visit plan should be updated on a regular basis.
2. Protection from the weather elements relates to the normal prevailing local weather elements that are expected throughout any twelve-month period. Aircraft hangar and component workshop structures should prevent the ingress of rain, hail, ice, snow, wind and dust etc. Aircraft hangar and component workshop floors should be sealed to minimise dust generation.
3. For line maintenance of aircraft, hangars are not essential but it is recommended that access to hangar accommodation be demonstrated for usage during inclement weather for minor scheduled work and lengthy defect rectification.
4. Aircraft maintenance staff should be provided with an area where they may study maintenance instructions and complete maintenance records in a proper manner.

AMC 145.A.25(b) Facility requirements

It is acceptable to combine any or all of the office accommodation requirements into one office subject to the staff having sufficient room to carry out the assigned tasks.

In addition, as part of the office accommodation, aircraft maintenance staff should be provided with an area where they may study maintenance instructions and complete maintenance records in a proper manner.

AMC 145.A.25(d) Facility requirements

1. Storage facilities for serviceable aircraft components should be clean, well-ventilated and maintained at a constant dry temperature to minimise the effects of condensation. Manufacturer's storage recommendations should be followed for those aircraft components identified in such published recommendations.
2. Storage racks should be strong enough to hold aircraft components and provide sufficient support for large aircraft components such that the component is not distorted during storage.
3. All aircraft components, wherever practicable, should remain packaged in protective material to minimise damage and corrosion during storage.

145.A.30 Personnel Requirements

- (a) The organisation shall appoint an accountable manager who has corporate authority for ensuring that all maintenance required by the customer can be financed and carried out to the standard required by this Part. The accountable manager shall:
 1. ensure that all necessary resources are available to accomplish maintenance in accordance with 145.A.65(b) to support the organisation approval.
 2. establish and promote the safety and quality policy specified in 145.A.65(a).
 3. demonstrate a basic understanding of this Part.
- (b) The organisation shall nominate a person or group of persons, whose responsibilities include ensuring that the organisation complies with this Part. Such person(s) shall ultimately be responsible to the accountable manager.

1. The person or persons nominated shall represent the maintenance management structure of the organisation and be responsible for all functions specified in this Part.
 2. The person or persons nominated shall be identified and their credentials submitted in a form and manner established by the CAAB.
 3. The person or persons nominated shall be able to demonstrate relevant knowledge, background and satisfactory experience related to aircraft or component maintenance and demonstrate a working knowledge of this Part.
 4. Procedures shall make clear who deputises for any particular person in the case of lengthy absence of the said person.
- (c) The accountable manager under paragraph (a) shall appoint a person with responsibility for monitoring the quality system, including the associated feedback system as required by 145.A.65(c). The appointed person shall have direct access to the accountable manager to ensure that the accountable manager is kept properly informed on quality and compliance matters.
- (d) The organisation shall have a maintenance man-hour plan showing that the organisation has sufficient staff to plan, perform, supervise, inspect and quality monitor the organisation in accordance with the approval. In addition the organisation shall have a procedure to reassess work intended to be carried out when actual staff availability is less than the planned staffing level for any particular work shift or period.
- (e) The organisation shall establish and control the competence of personnel involved in any maintenance, management and/or quality audits in accordance with a procedure and to a standard agreed by the CAAB. In addition to the necessary expertise related to the job function, competence must include an understanding of the application of human factors and human performance issues appropriate to that person's function in the organisation.

"Human factors" means principles which apply to aeronautical design, certification, training, operations and maintenance and which seek safe interface between the human and other system components by proper consideration of human performance.

"Human performance" means human capabilities and limitations which have an impact on the safety and efficiency of aeronautical operations.

- (f) The organisation shall ensure that personnel who carry out and/or control a continued airworthiness non-destructive test of aircraft structures and/or components are appropriately qualified for the particular non-destructive test in accordance with the European or equivalent Standard recognised by the CAAB. Personnel who carry out any other specialised task shall be appropriately qualified in accordance with officially recognised Standards. By derogation to this paragraph those personnel specified in paragraphs (g) and (h)(1) and (h)(2), qualified in category B1 or B3 in accordance with Part-66 may carry out and/or control colour contrast dye penetrant tests.
- (g) Any organisation maintaining aircraft, except where stated otherwise in point (j), shall in the case of aircraft line maintenance, have appropriate aircraft rated certifying staff qualified as category B1, B2, B3, as appropriate, in accordance with Part-66 and point 145.A.35.

In addition such organisations may also use appropriately task trained certifying staff holding the privileges described in points 66.A.20(a)(1) and 66.A.20(a)(3)(ii) and qualified in accordance with Part-66 and part 145.A.35 to carry out minor scheduled line maintenance and simple defect rectification. The availability of such certifying staff shall not replace the need for category B1, B2, B3 certifying staff, as appropriate.

- (h) Any organisation maintaining aircraft, except where stated otherwise in paragraph (j) shall:
1. In the case of base maintenance of complex motor-powered aircraft, have appropriate aircraft type rated certifying staff qualified as category C in accordance with Part-66 and 145.A.35. In addition the organisation shall have sufficient aircraft type rated staff qualified as category B1, B2 as appropriate in accordance with Part-66 and 145.A.35 to support the category C certifying staff.
 - (i) B1 and B2 support staff shall ensure that all relevant tasks or inspections have been carried out to the required standard before the category C certifying staff issues the certificate of release to service.
 - (ii) The organisation shall maintain a register of any such B1 and B2 support staff.

-
- (iii) The category C certifying staff shall ensure that compliance with paragraph (i) has been met and that all work required by the customer has been accomplished during the particular base maintenance check or work package, and shall also assess the impact of any work not carried out with a view to either requiring its accomplishment or agreeing with the operator to defer such work to another specified check or time limit.
- 2. in the case of base maintenance of aircraft other than complex motor-powered aircraft have either:
 - (i) appropriate aircraft rated certifying staff qualified as category B1, B2, B3, as appropriate, in accordance with Part-66 and point 145.A.35 or,
 - (ii) appropriate aircraft rated certifying staff qualified in category C assisted by support staff as specified in point 145.A.35(a)(i).
- (i) Component Certifying staff shall comply with National Regulations.
 - (j) By derogation to paragraphs (g) and (h), in relation to the obligation to comply with Part-66, the organisation may use certifying staff qualified in accordance with the following provisions:
 - 1. For organisation facilities located outside the CAAB territory certifying staff may be qualified in accordance with the national aviation regulations of the State in which the organisation facility is registered subject to the conditions specified in Appendix IV to this Part.-
 - 2. For line maintenance carried out at a line station of an organisation which is located outside CAAB territory, the certifying staff may be qualified in accordance with the national aviation regulations of the State in which the line station is based, subject to the conditions specified in Appendix IV to this Part.
 - 3. For a repetitive pre-flight airworthiness directive which specifically states that the flight crew may carry out such airworthiness directive, the organisation may issue a limited certification authorisation to the aircraft commander and/or the flight engineer on the basis of the flight crew licence held. However, the organisation shall ensure that sufficient practical training has been carried out to ensure that such aircraft commander or flight engineer can accomplish the airworthiness directive to the required standard.

4. In the case of aircraft operating away from a supported location the organisation may issue a limited certification authorisation to the commander and/or the flight engineer on the basis of the flight crew licence held subject to being satisfied that sufficient practical training has been carried out to ensure that the commander or flight engineer can accomplish the specified task to the required standard. The provisions of this paragraph shall be detailed in an exposition procedure.
5. In the following unforeseen cases, where an aircraft is grounded at a location other than the main base where no appropriate certifying staff is available, the organisation contracted to provide maintenance support may issue a one-off certification authorisation:
 - (i) to one of its employees holding equivalent type authorisations on aircraft of similar technology, construction and systems; or
 - (ii) to any person with not less than five years maintenance experience and holding a valid ICAO aircraft maintenance licence rated for the aircraft type requiring certification provided there is no organisation appropriately approved under this Part at that location and the contracted organisation obtains and holds on file evidence of the experience and the licence of that person.

All such cases as specified in this subparagraph shall be reported to the CAAB within seven days of the issuance of such certification authorisation. The organisation issuing the one-off authorisation shall ensure that any such maintenance that could affect flight safety is re-checked by an appropriately approved organisation.

AMC 145.A.30(a) Personnel requirements

With regard to the accountable manager, it is normally intended to mean the chief executive officer of the approved maintenance organisation, who by virtue of position has overall (including in particular financial) responsibility for running the organisation. The accountable manager may be the accountable manager for more than one organisation and is not required to be necessarily knowledgeable on technical matters as the maintenance organisation exposition defines the maintenance standards. When the accountable manager is not the chief executive officer the CAAB will need to be assured that such an accountable manager has direct access to chief executive officer and has a sufficiency of 'maintenance funding' allocation.

AMC1 145.A.30(b) Personnel requirements

1. Dependent upon the size of the organisation, the Part-145 functions may be subdivided under individual managers or combined in any number of ways.
2. The organisation should have, dependent upon the extent of approval, a base maintenance manager, a line maintenance manager, a workshop manager and a quality manager, all of whom should report to the accountable manager except in small Part-145 organisation where any one manager may also be the accountable manager, as determined by the CAAB he/she may also be the line maintenance manager or the workshop manager.
3. The base maintenance manager is responsible for ensuring that all maintenance required to be carried out in the hangar, plus any defect rectification carried out during base maintenance, is carried out to the design and quality standards specified in 145.A.65 (b). The base maintenance manager is also responsible for any corrective action resulting from the quality compliance monitoring of 145.A.65(c).
4. The line maintenance manager is responsible for ensuring that all maintenance required to be carried out on the line including line defect rectification is carried out to the standards specified in 145.A.65(b) and also responsible for any corrective action resulting from the quality compliance monitoring of 145.A.65(c).
5. The workshop manager is responsible for ensuring that all work on aircraft components is carried out to the standards specified in 145.A.65(b) and also responsible for any corrective action resulting from the quality compliance monitoring of 145.A.65(c).
6. The quality manager's responsibility is specified in 145.A.30(c).
7. Notwithstanding the example sub-paragraphs 2 - 6 titles, the organisation may adopt any title for the foregoing managerial positions but should identify to the CAAB the titles and persons chosen to carry out these functions.
8. Where an organisation chooses to appoint managers for all or any combination of the identified Part-145 functions because of the size of the undertaking, it is necessary that these managers report ultimately through either the base maintenance manager or line maintenance manager or workshop manager or quality manager, as appropriate, to the accountable manager.

Note: Certifying staff may report to any of the managers specified depending upon which type of control the approved maintenance organisation uses (for example licensed engineers/independent inspection/dual function supervisors etc.) so long as the quality compliance monitoring staff specified in 145.A.65(c)(1) remain independent.

AMC2 145.A.30(b) Personnel requirements

Knowledge, Background and Experience of Nominated Person(s)

The person or persons to be nominated in accordance with points (b) of 145.A.30 should have:

- (a) practical experience and expertise in the application of aviation safety standards and safe operating practices;
- (b) knowledge of:
 - (1) human factors principles;
 - (2) safety management systems and quality assurance;
- (c) five years relevant work experience in aviation of which at least two years should be in an appropriate position in civil organization;
or
five years' work experience in an airworthiness inspection organisation;
- (d) a relevant engineering or technical degree, or an aircraft technician or maintenance engineer qualification with additional education that is acceptable to the CAAB. 'Relevant engineering or technical degree' means a degree from aeronautical, mechanical, electrical, electronic, avionics or other studies that are relevant to the maintenance and/or continuing airworthiness of aircraft/aircraft components.

The provision set out in the first paragraph of point (d) may be replaced by 2 years of experience in addition to those already recommended by paragraph (c) above. These 2 years should cover an appropriate combination of experience in tasks/activities related to maintenance and/or continuing airworthiness management and/or the surveillance of such tasks.

For the person to be nominated in accordance with 145.A.30 (b), in the case where the organisation holds one or more additional organisation certificates issued by CAAB and that person has already an equivalent position (i.e. quality manager) under the additional certificate(s) held, the provisions set out in the first two paragraphs of point (d) may be replaced by the completion of a specific training programme acceptable to the CAAB to gain an adequate understanding of maintenance standards and continuing airworthiness concepts and principles;

- (e) thorough knowledge of the organisation's MOE and safety policy;
- (f) knowledge of a relevant sample of the type(s) of aircraft or components gained through a formalised training course. These courses could be provided by a Part-147 organisation, by the manufacturer, by the Part-145 organisation or by any other organisation accepted by the CAAB. Aircraft/engine type training courses should be at least at a level equivalent to the Part-66 Appendix III Level 1 General Familiarisation.

‘Relevant sample’ means that these courses should cover typical aircraft or components that are within the scope of work of the organisation.

For any other aircraft of 2730 kg MTOM or less, the formalised training courses may be replaced by a demonstration of the required knowledge by providing documented evidence, or by an assessment acceptable to the CAAB. This assessment should be recorded;

- (g) knowledge of the relevant maintenance methods (and how they are applied in the organisation) and/or specific knowledge relevant to the area for which the person will be nominated;
- (h) knowledge of the applicable regulations;
- (i) adequate language and communication skills.

AMC 145.A.30(c) Personnel requirements

Monitoring the quality system includes requesting remedial action as necessary by the accountable manager and the nominated persons referred to in 145.A.30 (b).

AMC 145.A.30(d) Personnel requirements

1. Has sufficient staff means that the organisation employs or contracts competent staff, as detailed in the man-hour plan, of which at least half the staff that perform maintenance in each workshop, hangar or flight line on any shift should be employed to ensure organisational stability. For the purpose of meeting a specific operational necessity, a temporary increase of the proportion of contracted staff may be permitted to the organisation by the CAAB in accordance with an approved procedure which should describe the extent, specific duties, and responsibilities for ensuring adequate organisation stability. For the purpose of this subparagraph, employed means the person is directly employed as an individual by the maintenance organisation approved under Part-145, whereas contracted means the person is employed by another organisation and contracted by that organisation to the maintenance organisation approved under Part-145.
2. The maintenance man-hour plan should take into account all maintenance activities carried out outside the scope of the Part-145 approval.

The planned absence (for training, vacations, etc.) should be considered when developing the man-hour plan.
3. The maintenance man-hour plan should relate to the anticipated maintenance workload except that when the organisation cannot predict such workload, due to the short-term nature of its contracts, then such plan should be based upon the minimum maintenance workload needed for commercial viability. Maintenance workload includes all necessary work such as, but not limited to, planning, maintenance record checks, production of worksheets/cards in paper or electronic form, accomplishment of maintenance, inspection and the completion of maintenance records.
4. In the case of aircraft base maintenance, the maintenance man-hour plan should relate to the aircraft hangar visit plan as specified in AMC 145.A.25 (a).
5. In the case of aircraft component maintenance, the maintenance man-hour plan should relate to the aircraft component planned maintenance as specified in 145.A.25 (a) (2).

6. The quality monitoring compliance function man-hours should be sufficient to meet the requirement of 145.A.65(c) which means taking into account AMC 145.A.65(c). Where quality monitoring staff perform other functions, the time allocated to such functions needs to be taken into account in determining quality monitoring staff numbers.
7. The maintenance man-hour plan should be reviewed at least every 3 months and updated when necessary.
8. Significant deviation from the maintenance man-hour plan should be reported through the departmental manager to the quality manager and the accountable manager for review. Significant deviation means more than a 25% shortfall in available man-hours during a calendar month for any one of the functions specified in 145.A.30 (d).

AMC 1 145.A.30(e)

Competence should be defined as a measurable skill or standard of performance, knowledge and understanding, taking into consideration attitude and behaviour.

The referenced procedure requires amongst others that planners, mechanics, specialised services staff, supervisors, certifying staff and support staff, whether employed or contracted, are assessed for competence before unsupervised work commences and competence is controlled on a continuous basis.

Competence should be assessed by evaluation of:

- on-the-job performance and/or testing of knowledge by appropriately qualified personnel, and
- records for basic, organisational, and/or product type and differences training, and
- experience records.

Validation of the above could include a confirmation check with the organisation(s) that issued such document(s). For that purpose, experience/training may be recorded in a document such as a log book or based on the suggested template in a GM 3 to 145.A.30 (e).

As a result of this assessment, an individual's qualification should determine:

- which level of ongoing supervision would be required or whether unsupervised work could be permitted.
- whether there is a need for additional training.

A record of such qualification and competence assessment should be kept.

This should include copies of all documents that attest to qualification, such as the licence and/or any authorisation held, as applicable.

For a proper competence assessment of its personnel, the organisation should consider that:

1. In accordance with the job function, adequate initial and recurrent training should be provided and recorded to ensure continued competence so that it is maintained throughout the duration of employment/contract.
2. All staff should be able to demonstrate knowledge of and compliance with the maintenance organisation procedures, as applicable to their duties.
3. All staff should be able to demonstrate an understanding of human factors and human performance issues in relation with their job function and be trained as per AMC2 145.A.30 (e).
4. To assist in the assessment of competence and to establish the training needs analysis, job descriptions are recommended for each job function in the organisation. Job descriptions should contain sufficient criteria to enable the required competence assessment.
5. Criteria should allow the assessment to establish that, among others (titles might be different in each organisation):
 - Managers are able to properly manage the work output, processes, resources and priorities described in their assigned duties and responsibilities in a safe compliant manner in accordance with regulations and organisation procedures.
 - Planners are able to interpret maintenance requirements into maintenance tasks, and have an understanding that they have no authority to deviate from the maintenance data.
 - Supervisors are able to ensure that all required maintenance tasks are carried out and, where not completed or where it is evident that a particular maintenance task cannot be carried out to the maintenance data, then such problems will be reported to the 145.A.30(c) person for appropriate action. In addition, for those supervisors, who also carry out maintenance tasks, that they understand such tasks should not be undertaken when incompatible with their management responsibilities.

-
- Mechanics are able to carry out maintenance tasks to any standard specified in the maintenance data and will notify supervisors of defects or mistakes requiring rectification to re-establish required maintenance standards.
 - Specialised services staff are able to carry out specialised maintenance tasks to the standard specified in the maintenance data.. They should be able to communicate with supervisors and report accurately when necessary.
 - Support staffs are able to determine that relevant tasks or inspections have been carried out to the required standard.
 - Certifying staff are able to determine when the aircraft or aircraft component is ready to release to service and when it should not be released to service.
 - Quality audit staffs are able to monitor compliance with Part-145 identifying non-compliance in an effective and timely manner so that the organisation may remain in compliance with Part-145.

Competence assessment should be based upon the procedure specified in GM 2 to 145.A.30(e).

AMC 2 145.A.30(e)

In respect to the understanding of the application of human factors and human performance issues, all maintenance organisation personnel should have received an initial and continuation human factors training. This should concern to a minimum:

- Post-holders, managers, supervisors;
- Certifying staff, support staff and mechanics;
- Technical support personnel such as planners, engineers, technical record staff;
- Quality control/assurance staff;
- Specialised services staff;
- Human factors staff/human factors trainers;
- Store department staff, purchasing department staff;
- Ground equipment operators.

1. Initial human factors training should cover all the topics of the training syllabus specified in GM 145.A.30(e) either as a dedicated course or else integrated within other training. The syllabus may be adjusted to reflect the particular nature of the organisation. The syllabus may also be adjusted to meet the particular nature of work for each function within the organisation. For example:
 - small organisations not working in shifts may cover in less depth subjects related to teamwork and communication;
 - planners may cover in more depth the scheduling and planning objective of the syllabus and in less depth the objective of developing skills for shift working.

All personnel, including personnel being recruited from any other organisation should receive initial human factors training compliant with the organisation's training standards prior to commencing actual job function, unless their competence assessment justifies that there is no need for such training. Newly directly employed personnel working under direct supervision may receive training within 6 months after joining the maintenance organisation.

2. The purpose of human factors continuation training is primarily to ensure that staff remain current in terms of human factors and also to collect feedback on human factors issues. Consideration should be given to the possibility that such training has the involvement of the quality department. There should be a procedure to ensure that feedback is formally passed from the trainers to the quality department to initiate action where necessary.

Human factors continuation training should be of an appropriate duration in each two year period in relation to relevant quality audit findings and other internal/external sources of information on human errors in maintenance available to the organisation.

3. Human factors training may be conducted by the maintenance organisation itself, or independent trainers, or any training organisations acceptable to the CAAB.
4. The human factors training procedures should be specified in the maintenance organisation exposition.

AMC 3 145.A.30(e)

Additional training in fuel tank safety as well as associated inspection standards and maintenance procedures should be required for maintenance organisations' technical personnel, especially technical personnel involved in the compliance of CDCCL tasks.

CAAB's Guidance is provided for training to maintenance organisation personnel in Appendix IV to AMC to 145.A.30(e).

AMC 4 145.A.30(e)

Competence assessment should include the verification for the need of additional EWIS training when relevant.

In the absence of specific ANO Part-145 guidance, guidance of EASA AMC 20-22 may be used for EWIS training programme to maintenance organisation personnel.

AMC 145.A.30(f) Personnel requirements

1. Continued airworthiness non-destructive testing means such testing specified by the type certificate holder /aircraft or engine or propeller manufacturer in accordance with the maintenance data as specified in 145.A.45 for in service aircraft/aircraft components for the purpose of determining the continued fitness of the product to operate safely.
2. Appropriately qualified means to Level 1, 2 or 3 as defined by the European Standard EN 4179 dependent upon the non-destructive testing function to be carried out or any standard recognised as equivalent by CAAB.
3. Notwithstanding the fact that Level 3 personnel may be qualified via EN 4179 or any standard recognised by the CAAB to establish and authorise methods, techniques, etc., this does not permit such personnel to deviate from methods and techniques published by the type certificate holder/manufacturer in the form of continued airworthiness data, such as in non-destructive test manuals or service bulletins, unless the manual or service bulletin expressly permits such deviation.
4. All examinations should be conducted by personnel or organisations under the control of an organisation (NDT board for example) recognised by the CAAB.

5. Particular non-destructive test means any one or more of the following; Dye penetrant, magnetic particle, eddy current, ultrasonic and radiographic methods including X ray and gamma ray.
6. It should be noted that new methods are and will be developed, such as, but not limited to thermography and shearography, which are not specifically addressed in the standards recognised by the CAAB. Until the time this agreed standard is established, such methods should be carried out in accordance with the particular equipment manufacturer's recommendations including any training and examination process to ensure competence of the personnel in the process.
7. Any maintenance organisation approved under Part-145 that carries out NDT should establish NDT specialist qualification procedures detailed in the exposition and accepted by the CAAB.
8. Boroscopy and other techniques such as delamination coin tapping are non-destructive inspections rather than non-destructive testing. Notwithstanding such differentiation, the maintenance organisation should establish an exposition procedure accepted by the CAAB to ensure that personnel who carry out and interpret such inspections are properly trained and assessed for their competence in the process. Non-destructive inspections, not being considered as NDT by Part-145 are not listed in Appendix II under class rating D1.
9. The referenced standards, methods, training and procedures should be specified in the maintenance organisation exposition.
10. Any such personnel who intend to carry out and/or control a non-destructive test for which they were not qualified prior to the effective date of Part-145 should qualify for such non-destructive test in accordance with EN 4179 or a standard recognised as equivalent or acceptable to the CAAB.
11. In this context officially recognised standard means those standards established or published by an official body whether having legal personality or not, which are widely recognised by the air transport sector as constituting good practice.

AMC 145.A.30(g) Personnel requirements

1. For the purposes of 66.A.20(a)(1) and 66.A.20(a)(3)(ii) personnel, minor scheduled line maintenance means any minor scheduled inspection/check up to and including a weekly check specified in the aircraft maintenance programme. For aircraft maintenance programmes that do not specify a weekly check, the CAAB will determine the most significant check that is considered equivalent to a weekly check.
2. Typical tasks permitted after appropriate task training to be carried out by the 66.A.20(a)(1) and the 66.A.20(a)(3)(ii) personnel for the purpose of these personnel issuing an aircraft certificate of release to service as specified in 145.A.50 as part of minor scheduled line maintenance or simple defect rectification are contained in the following list:
 - (a) Replacement of wheel assemblies.
 - (b) Replacement of wheel brake units.
 - (c) Replacement of emergency equipment.
 - (d) Replacement of ovens, boilers and beverage makers.
 - (e) Replacement of internal and external lights, filaments and flash tubes.
 - (f) Replacement of windscreen wiper blades.
 - (g) Replacement of passenger and cabin crew seats, seat belts and harnesses.
 - (h) Closing of cowlings and refitment of quick access inspection panels.
 - (i) Replacement of toilet system components but excluding gate valves.
 - (j) Simple repairs and replacement of internal compartment doors and placards but excluding doors forming part of a pressure structure.
 - (k) Simple repairs and replacement of overhead storage compartment doors and cabin furnishing items.
 - (l) Replacement of static wicks.
 - (m) Replacement of aircraft main and APU aircraft batteries.
 - (n) Replacement of in-flight entertainment system components other than public address.

- (o) Routine lubrication and replenishment of all system fluids and gases.
- (p) The de-activation only of sub-systems and aircraft components as permitted by the operator's minimum equipment list where such de-activation is agreed by the CAAB as a simple task.
- (q) Inspection for and removal of de-icing/anti-icing fluid residues, including removal/closure of panels, cowls or covers or the use of special tools.
- (r) Any other task agreed by the CAAB as a simple task for a particular aircraft type. This may include defect deferment when all the following conditions are met:
 - There is no need for troubleshooting; and
 - The task is in the MEL; and
 - The maintenance action required by the MEL is agreed by the CAAB to be simple.

In the particular case of helicopters, and in addition to the items above, the following:

- (s) removal and installation of Helicopter Emergency Medical Service (HEMS) simple internal medical equipment.
- (t) removal and installation of external cargo provisions (i.e., external hook, mirrors) other than the hoist.
- (u) removal and installation of quick release external cameras and search lights.
- (v) removal and installation of emergency float bags, not including the bottles.
- (w) removal and installation of external doors fitted with quick release attachments.
- (x) removal and installation of snow pads/skid wear shoes/slump protection pads.

No task which requires troubleshooting should be part of the authorised maintenance actions. Release to service after rectification of deferred defects should be permitted as long as the task is listed above.

3. The requirement of having appropriate aircraft rated certifying staff qualified as category B1, B2, B3, as appropriate, in the case of aircraft line maintenance does not imply that the organisation must have B1, B2 and B3 personnel at every line station. The MOE should have a procedure on how to deal with defects requiring B1, B2 or B3 certifying staff.
4. CAAB may accept that in the case of aircraft line maintenance an organisation has only B1, B2 or B3 certifying staff, as appropriate, provided that the CAAB is satisfied that the scope of work, as defined in the Maintenance Organisation Exposition, does not need the availability of all B1, B2 and B3 certifying staff. Special attention should be taken to clearly limit the scope of scheduled and non-scheduled line maintenance (defect rectification) to only those tasks that can be certified by the available certifying staff category.

AMC 145.A.30(h) Personnel requirements

In accordance with 145.A.30(h) and 145.A.35, the qualification requirements (basic licence, aircraft ratings, recent experience and continuation training) are identical for certifying staff and for support staff. The only difference is that support staff cannot hold certification privileges when performing this role since during base maintenance the release to service will be issued by category C certifying staff.

Nevertheless, the organisation may use as support staff (for base maintenance) persons who already hold certification privileges for line maintenance.

AMC 145.A.30(j)(4) Personnel requirements

1. For the issue of a limited certification authorisation the commander or flight engineer should hold either a valid air transport pilots license (ATPL), commercial pilots license (CPL) or flight engineer (F/EL) licence in accordance with the CAAB's flight crew licensing system on the aircraft type. In addition the limited certification authorisation is subject to the maintenance organisation exposition containing procedures to address the personnel requirements of 145.A.30 (e) and associated AMC and guidance material.

Such procedures should include as a minimum:

- (a) Completion of adequate maintenance airworthiness regulation training.

- (b) Completion of adequate task training for the specific task on the aircraft. The task training should be of sufficient duration to ensure that the individual has a thorough understanding of the task to be completed and will involve training in the use of associated maintenance data.
- (c) Completion of the procedural training as specified in Part-145.

The above procedures should be specified in the maintenance organisation exposition and be accepted by the CAAB.

2.(i) Typical tasks that may be certified and/or carried out by the commander holding an ATPL or CPL are minor maintenance or simple checks included in the following list:

- (a) Replacement of internal lights, filaments and flash tubes.
- (b) Closing of cowlings and refitment of quick access inspection panels.
- (c) Role changes e.g. stretcher fit, dual controls, FLIR, doors, photographic equipment etc.
- (d) Inspection for and removal of de-icing/anti-icing fluid residues, including removal/closure of panels, cowls or covers that are easily accessible but not requiring the use of special tools.
- (e) Any check / replacement involving simple techniques consistent with this AMC and as agreed by the CAAB.

2.(ii) Holders of a valid Flight engineers licence meeting the CAAB Flight Crew Licensing System, on the aircraft type may only exercise this limited certification authorisation privilege when performing the duties of a flight engineer.

In addition to paragraph 2(i)(a) to (e) other typical minor maintenance or simple defect rectification tasks that may be carried out are included in the following list:

- (a) Replacement of wheel assemblies.
- (b) Replacement of simple emergency equipment that is easily accessible.
- (c) Replacement of ovens, boilers and beverage makers.
- (d) Replacement of external lights.

-
- (e) Replacement of passenger and cabin crew seats, seat belts and harnesses.
 - (f) Simple replacement of overhead storage compartment doors and cabin furnishing items.
 - (g) Replacement of static wicks.
 - (h) Replacement of aircraft main and APU aircraft batteries.
 - (i) Replacement of in-flight entertainment system components other than public address.
 - (j) The de-activation only of sub-systems and aircraft components as permitted by the operator's minimum equipment list where such de-activation is agreed by the CAAB as a simple task.
 - (k) Re-setting of tripped circuit breakers under the guidance of maintenance control.
 - (l) Any other task agreed by CAAB as a simple task for a particular aircraft type.
3. The authorisation should have a finite life of twelve months subject to satisfactory re-current training on the applicable aircraft type.

AMC 145.A.30(j)(5) Personnel requirements

1. For the purposes of this sub-paragraph “unforeseen” means that the aircraft grounding could not reasonably have been predicted by the operator because the defect was unexpected due to being part of a hitherto reliable system.
2. A one-off authorisation should only be considered for issue by the quality department of the contracted organisation after it has made a reasoned judgement that such a requirement is appropriate under the circumstances and at the same time maintaining the required airworthiness standards. The organisation’s quality department will need to assess each situation individually prior to the issuance of a one-off authorisation
3. A one-off authorisation should not be issued where the level of certification required could exceed the knowledge and experience level of the person it is issued to. In all cases, due consideration should be given to the complexity of the work involved and the availability of required tooling and/or test equipment needed to complete the work.

AMC 145.A.30(j)(5)(i) Personnel requirements

In those situations where the requirement for a one-off authorisation to issue a CRS for a task on an aircraft type for which certifying staff does not hold a type-rated authorisation has been identified, the following procedure is recommended:

1. Flight crew should communicate full details of the defect to the operator's supporting maintenance organisation. If necessary, the supporting maintenance organisation will then request the use of a one-off authorisation from the quality department.
2. When issuing a one-off authorisation, the quality department of the organisation should verify that:
 - (a) Full technical details relating to the work required to be carried out have been established and passed on to the certifying staff.
 - (b) The organisation has an approved procedure in place for coordinating and controlling the total maintenance activity undertaken at the location under the authority of the one-off authorisation.
 - (c) The person to whom a one-off authorisation is issued has been provided with all the necessary information and guidance relating to maintenance data and any special technical instructions associated with the specific task undertaken. A detailed step by step worksheet has been defined by the organisation, communicated to the one-off authorisation holder.
 - (d) The person holds authorisations of equivalent level and scope on other aircraft type of similar technology, construction and systems.
3. The one-off authorisation holder should sign off the detailed step by step worksheet when completing the work steps. The completed tasks should be verified by visual examination and/or normal system operation upon return to an appropriately approved Part-145 maintenance facility.

AMC 145.A.30(j)(5)(ii) Personnel requirements

This paragraph addresses staff not employed by the maintenance organisation who meet the requirements of 145.A.30 (j) (5). In addition to the items listed in AMC 145.A.30(j) (5) (i), paragraph 1, 2(a), (b) and (c) and 3 the quality department of the organisation may issue such one-off authorisation providing full qualification details relating to the proposed certifying personnel are verified by the quality department and made available at the location.

145.A.35 Certifying Staff and Support Staff

- (a) In addition to the appropriate requirements of 145.A.30(g) and (h), the organisation shall ensure that certifying staff and support staff have an adequate understanding of the relevant aircraft and/or components to be maintained together with the associated organisation procedures. In the case of certifying staff, this shall be accomplished before the issue or re-issue of the certification authorisation.
- (i) ‘Support staff’ means those staff holding a Part-66 aircraft maintenance licence in category B1, B2 and/or B3 with the appropriate aircraft ratings, working in a base maintenance environment while not necessarily holding certification privileges.
- (ii) ‘Relevant aircraft and/or components’, means those aircraft or components specified in the particular certification authorisation.
- (iii) ‘Certification authorisation’ means the authorisation issued to certifying staff by the organisation and which specifies the fact that they may sign certificates of release to service within the limitations stated in such authorisation on behalf of the approved organisation.
- (b) Except for the cases listed in 145.A.30(j) and 66.A.20(a)3(ii) the organisation may only issue a certification authorisation to certifying staff in relation to the basic categories or subcategories and, except for the category A licence, any type rating listed on the aircraft maintenance licence as required by Part-66, subject to the licence remaining valid throughout the validity period of the authorisation and the certifying staff remaining in compliance with Part-66.
- (c) The organisation shall ensure that all certifying staff and support staff are involved in at least six months of actual relevant aircraft or component maintenance experience in any consecutive two year period.

For the purpose of this paragraph "involved in actual relevant aircraft or component maintenance" means that the person has worked in an aircraft or component maintenance environment and has either exercised the privileges of the certification authorisation and/or has actually carried out maintenance on at least some of the aircraft type or aircraft group systems specified in the particular certification authorisation.

-
- (d) The organisation shall ensure that all certifying staff and support staff receive sufficient continuation training in each two year period to ensure that such staff have up-to-date knowledge of relevant technology, organisation procedures and human factor issues.
- (e) The organisation shall establish a programme for continuation training for certifying staff and support staff, including a procedure to ensure compliance with the relevant paragraphs of 145.A.35 as the basis for issuing certification authorisations under this Part to certifying staff, and a procedure to ensure compliance with Part 66.
- (f) Except where any of the unforeseen cases of 145.A.30(j)(5) apply, the organisation shall assess all prospective certifying staff for their competence, qualification and capability to carry out their intended certifying duties in accordance with a procedure as specified in the exposition prior to the issue or re-issue of a certification authorisation under this Part.
- (g) When the conditions of paragraphs (a), (b), (d), (f) and, where applicable, paragraph (c) have been fulfilled by the certifying staff, the organisation shall issue a certification authorisation that clearly specifies the scope and limits of such authorisation. Continued validity of the certification authorisation is dependent upon continued compliance with paragraphs (a), (b), (d), and where applicable, paragraph (c).
- (h) The certification authorisation must be in a style that makes its scope clear to the certifying staff and any official of the CAAB who has the responsibility for oversight of maintained aircraft or component, who may require to examine the authorisation.
- (i) The person responsible for the quality system shall also remain responsible on behalf of the organisation for issuing certification authorisations to certifying staff. Such person may nominate other persons to actually issue or revoke the certification authorisations in accordance with a procedure as specified in the exposition.
- (j) The organisation shall maintain a record of all certifying staff and support staff, which shall contain:
1. the details of any aircraft maintenance licence held under Part-66; and

2. all relevant training completed; and
3. the scope of the certification authorisations issued, where relevant; and
4. particulars of staff with limited or one-off certification authorisations.

The organisation shall retain the record for at least three years after the staff referred to in this paragraph have ceased employment with the organisation or as soon as the authorisation has been withdrawn. In addition, upon request, the maintenance organisation shall furnish the staff referred to in this paragraph with a copy of their personal record on leaving the organisation.

The staff referred to in this paragraph shall be given access on request to their personal records as detailed above.

- (k) The organisation shall provide certifying staff with a copy of their certification authorisation in either a documented or electronic format.
- (l) Certifying staff shall produce their certification authorisation to any authorised person within 24 hours.
- (m) The minimum age for certifying staff and support staff is 21 years.
- (n) The holder of a category A aircraft maintenance licence may only exercise certification privileges on a specific aircraft type following the satisfactory completion of the relevant category A aircraft task training carried out by an organisation appropriately approved in accordance with Part-145 or Part-147. This training shall include practical hands on training and theoretical training as appropriate for each task authorised. Satisfactory completion of training shall be demonstrated by an examination or by workplace assessment carried out by the organisation.
- (o) The holder of a category B2 aircraft maintenance licence may only exercise the certification privileges described in point 66.A.20(a)(3)(ii) of Part-66 following the satisfactory completion of
 - (i) the relevant category A aircraft task training and
 - (ii) six months of documented practical experience covering the scope of the authorisation that will be issued.

The task training shall include practical hands on training and theoretical training as appropriate for each task authorised. Satisfactory completion of training shall be demonstrated by an examination or by workplace assessment. Task training and examination/assessment shall be carried out by the maintenance organisation issuing the certifying staff authorisation. The practical experience shall be also obtained within such maintenance organisation.

AMC 145.A.35(a) Certifying staff and support staff

1. Holding a Part-66 licence with the relevant type/group rating, or a national qualification in the case of components, does not mean by itself that the holder is qualified to be authorised as certifying staff and/or support staff. The organisation is responsible to assess the competence of the holder for the scope of maintenance to be authorised.
2. The sentence “the organisation shall ensure that certifying staff and support staff have an adequate understanding of the relevant aircraft and/or components to be maintained together with the associated organisation procedures” means that the person has received training and has been successfully assessed on:
 - the type of aircraft or component;
 - the differences on:
 - the particular model/variant;
 - the particular configuration.

The organisation should specifically ensure that the individual competencies have been established with regard to:

- relevant knowledge, skills and experience in the product type and configuration to be maintained, taking into account the differences between the generic aircraft type rating training that the person received and the specific configuration of the aircraft to be maintained.
- appropriate attitude towards safety and observance of procedures.
- knowledge of the associated organisation and operator procedures (i.e. handling and identification of components, MEL use, Technical Log use, independent checks, etc.).

3. Some special maintenance tasks may require additional specific training and experience, including but not limited to:
 - in-depth troubleshooting;
 - very specific adjustment or test procedures;
 - rigging;
 - engine run-up, starting and operating the engines, checking engine performance characteristics, normal and emergency engine operation, associated safety precautions and procedures;
 - extensive structural/system inspection and repair;
 - other specialised maintenance required by the maintenance programme.For engine run-up training, simulators and/or real aircraft should be used.
4. The satisfactory assessment of the competence should be conducted in accordance with a procedure approved by the CAAB (item 3.4 of the MOE, as described in AMC 145.A.70(a)).
5. The organisation should hold copies of all documents that attest the competence and recent experience for the period described in 145.A.35(j).

Additional information is provided in AMC 66.A.20(b)3.

AMC 145.A.35(b) Certifying staff and support staff

The organisation issues the certification authorisation when satisfied that compliance has been established with the appropriate paragraphs of Part-145 and Part-66. In granting the certification authorisation the maintenance organisation approved under Part-145 needs to be satisfied that the person holds a valid Part-66 aircraft maintenance licence.

AMC 145.A.35(c) Certifying staff and support staff

For the interpretation of “6 months of actual relevant aircraft maintenance experience in any consecutive 2-year period”, the provisions of AMC 66.A.20(b)2 are applicable.

AMC 145.A.35(d) Certifying staff and support staff

1. Continuation training is a two way process to ensure that certifying staff remain current in terms of procedures, human factors and technical knowledge and that the organisation receives feedback on the adequacy of its procedures and maintenance instructions. Due to the interactive nature of this training, consideration should be given to the possibility that such training has the involvement of the quality department to ensure that feedback is actioned. Alternatively, there should be a procedure to ensure that feedback is formally passed from the training department to the quality department to initiate action.
2. Continuation training should cover changes in relevant requirements such as Part-145, changes in organisation procedures and the modification standard of the products being maintained plus human factor issues identified from any internal or external analysis of incidents. It should also address instances where staff failed to follow procedures and the reasons why particular procedures are not always followed. In many cases the continuation training will reinforce the need to follow procedures and ensure that incomplete or incorrect procedures are identified to the company in order that they can be corrected. This does not preclude the possible need to carry out a quality audit of such procedures.
3. Continuation training should be of sufficient duration in each 2 year period to meet the intent of 145.A.35(d) and may be split into a number of separate elements. 145.A.35(d) requires such training to keep certifying staff updated in terms of relevant technology, procedures and human factors issues which means it is one part of ensuring quality. Therefore sufficient duration should be related to relevant quality audit findings and other internal / external sources of information available to the organisation on human errors in maintenance. This means that in the case of an organisation that maintains aircraft with few relevant quality audit findings, continuation training could be limited to days rather than weeks, whereas a similar organisation with a number of relevant quality audit findings, such training may take several weeks. For an organisation that maintains aircraft components, the duration of continuation training would follow the same philosophy but should be scaled down to reflect the more limited nature of the activity. For example certifying staff who release hydraulic pumps may only require a few hours of continuation training whereas those who release turbine engine may only require a few days of such training. The content of continuation training should be related to relevant quality audit findings and it is recommended that such training is reviewed at least once in every 24 month period.

4. The method of training is intended to be a flexible process and could, for example, include a Part-147 continuation training course, aeronautical college courses, internal short duration courses, seminars, etc. The elements, general content and length of such training should be specified in the maintenance organisation exposition unless such training is undertaken by an organisation approved under Part 147 when such details may be specified under the approval and cross referenced in the maintenance organisation exposition.

AMC 145.A.35(e) Certifying staff and support staff

The programme for continuation training should list all certifying staff and support staff and when training will take place, the elements of such training and an indication that it was carried out reasonably on time as planned. Such information should subsequently be transferred to the certifying staff and support staff record as required by 145.A.35 (j).

AMC 145.A.35(f) Certifying staff and support staff

As stated in 145.A.35 (f), except where any of the unforeseen cases of 145.A.30(j)(5) applies, all prospective certifying staff and support staff should be assessed for competence related to their intended duties in accordance with AMCs 1, 2, 3 and 4 to 145.A.30 (e), as applicable.

AMC 145.A.35 (j) Certifying staff and support staff

1. The following minimum information as applicable should be kept on record in respect of each certifying staff and support staff:
 - (a) Name
 - (b) Date of Birth
 - (c) Basic Training
 - (d) Type Training
 - (e) Continuation Training
 - (f) Experience
 - (g) Qualifications relevant to the authorisation.
 - (h) Scope of the authorisation

- (i) Date of first issue of the authorisation
 - (j) If appropriate - expiry date of the authorisation
 - (k) Identification Number of the authorisation
2. The record may be kept in any format but should be controlled by the organisation's quality department. This does not mean that the quality department should run the record system.
 3. Persons authorised to access the system should be maintained at a minimum to ensure that records cannot be altered in an unauthorised manner or that such confidential records become accessible to unauthorised persons.
 4. The CAAB is an authorised person when investigating the records system for initial and continued approval or when the CAAB has cause to doubt the competence of a particular person.

AMC 145.A.35(n) Certifying staff and support staff

1. It is the responsibility of the Part-145 organisation issuing the category A certifying staff authorisation to ensure that the task training received by this person covers all the tasks to be authorised. This is particularly important in those cases where the task training has been provided by a Part-147 organisation or by a Part-145 organisation different from the one issuing the authorisation.
2. “Appropriately approved in accordance with Part-147” means an organisation holding an approval to provide category A task training for the corresponding aircraft type.
3. “Appropriately approved in accordance with Part-145” means an organisation holding a maintenance organisation approval for the corresponding aircraft type.

AMC 145.A.35(o) Certifying staff and support staff

1. The privilege for a B2 licence holder to release minor scheduled line maintenance and simple defect rectification in accordance with 66.A.20(a)(3)(ii) can only be granted by the Part-145 approved organisation where the licence holder is employed/contracted after meeting all the requirements specified in 145.A.35(o). This privilege cannot be transferred to another Part-145 approved organisation.

2. When a B2 licence holder already holds a certifying staff authorisation containing minor scheduled line maintenance and simple defect rectification for a particular aircraft type, new tasks relevant to category A can be added to that type without requiring another 6 months of experience. However, task training (theoretical plus practical hands-on) and examination/assessment for these additional tasks is still required.
3. When the certifying staff authorisation intends to cover several aircraft types, the experience may be combined within a single 6-month period.

For the addition of new types to the certifying staff authorisation, another 6 months should be required unless the aircraft is considered similar per AMC 66.A.20(b)2 to the one already held.
4. The term “6 months of experience” may include full-time employment or part-time employment. The important aspect is that the person has been involved during a period of 6 months (not necessarily every day) in those tasks which are going to be part of the authorisation.

145.A.40 Equipment and Tools

- (a) The organisation shall have available and use the necessary equipment and tools to perform the approved scope of work.
 1. Where the manufacturer specifies a particular tool or equipment, the organisation shall use that tool or equipment, unless the use of alternative tooling or equipment is agreed by the CAAB via procedures specified in the exposition.
 2. Equipment and tools must be permanently available, except in the case of any tool or equipment that is so infrequently used that its permanent availability is not necessary. Such cases shall be detailed in an exposition procedure.
 3. An organisation approved for base maintenance shall have sufficient aircraft access equipment and inspection platforms/docking such that the aircraft can be properly inspected.
- (b) The organisation shall ensure that all tools, equipment and particularly test equipment, as appropriate, are controlled and calibrated according to an officially recognised standard at a frequency to ensure serviceability and accuracy. Records of such calibrations and traceability to the standard used shall be kept by the organisation.

AMC 145.A.40(a) Equipment and tools

Once the applicant for approval has determined the intended scope of work for consideration by the CAAB, it will be necessary to show that all tools and equipment as specified in the maintenance data can be made available when needed. All such tools and equipment that require to be controlled in terms of servicing or calibration by virtue of being necessary to measure specified dimensions and torque figures etc., should be clearly identified and listed in a control register including any personal tools and equipment that the organisation agrees can be used.

AMC 145.A.40(b) Equipment and tools

1. The control of these tools and equipment requires that the organisation has a procedure to inspect/service and, where appropriate, calibrate such items on a regular basis and indicate to users that the item is within any inspection or service or calibration time-limit. A clear system of labelling all tooling, equipment and test equipment is therefore necessary giving information on when the next inspection or service or calibration is due and if the item is unserviceable for any other reason where it may not be obvious. A register should be maintained for all precision tooling and equipment together with a record of calibrations and standards used.
2. Inspection, service or calibration on a regular basis should be in accordance with the equipment manufacturers' instructions except where the organisation can show by results that a different time period is appropriate in a particular case.
3. In this context officially recognised standard means those standards established or published by an official body whether having legal personality or not, which are widely recognised by the air transport sector as constituting good practice and by the CAAB.

145.A.42 Components

- (a) Classification of components. All components shall be classified into the following categories:
 - (i) Components which are in a satisfactory condition, released on a CAAB Form 1 or equivalent and marked in accordance with Subpart Q of the Part 21 unless otherwise specified in Part 21 or in this Part 145.

-
- (ii) Unserviceable components, which shall be maintained in accordance with this Regulation.
 - (iii) Components categorised as unsalvageable because they have reached their certified life limit or contain a non-repairable defect.
 - (iv) Standard parts used on an aircraft, engine, propeller or other aircraft component when specified in the maintenance data and accompanied by evidence of conformity traceable to the applicable standard.
 - (v) Material, both raw and consumable, used in the course of maintenance when the organisation is satisfied that the material meets the required specification and has appropriate traceability. All material shall be accompanied by documentation clearly relating to the particular material and containing a conformity to specification statement as well as the manufacturing and supplier source.
- (b) Components, standard parts and materials for installation
- (i) The organisation shall establish procedures for the acceptance of components, standard parts and materials for installation to ensure that components, standard parts and materials are in satisfactory condition and meet the applicable requirements of point (a).
 - (ii) The organisation shall establish procedures to ensure that components, standard parts and materials shall only be installed on an aircraft or a component when they are in satisfactory condition, meet the applicable requirements of point (a) and the applicable maintenance data specifies the particular component, standard part or material.
 - (iii) The organisation may fabricate a restricted range of parts to be used in the course of undergoing work within its own facilities, provided procedures are identified in the exposition.
- (c) Segregation of components
- (i) Unserviceable and unsalvageable components shall be segregated from serviceable components, standards parts and materials.
 - (ii) Unsalvageable components shall not be permitted to re-enter the component supply system, unless certified life limits have been extended or a repair solution has been approved in accordance with Part 21.

AMC1 145.A.42(a)(iii) Components

Unsalvageable Components

The following types of components should typically be classified as unsalvageable:

- (a) components with non-repairable defects, whether visible or not to the naked eye;
- (b) components that do not meet design specifications, and cannot be brought into conformity with such specifications;
- (c) components subjected to unacceptable modification or rework that is irreversible;
- (d) certified life-limited parts that have reached or exceeded their certified life limits, or have missing or incomplete records;
- (e) components whose airworthy condition cannot be restored due to exposure to extreme forces, heat or adverse environmental conditions;
- (f) components for which conformity with an applicable airworthiness directive cannot be accomplished;
- (g) components for which maintenance records and/or traceability to the manufacturer cannot be retrieved.

AMC1 145.A.42(a)(iv) Components

Standard Parts

- a) Standard parts are parts that are manufactured in complete compliance *with an established industry, CAAB* or other government specification that includes design, manufacturing, test and acceptance criteria, and uniform identification requirements. The specification should include all the information that is necessary to produce and verify conformity of the part. It should be published so that any party may manufacture the part. Examples of specifications are National Aerospace Standards (NAS), Army-Navy Aeronautical Standard (AN), Society of Automotive Engineers (SAE), SAE Sematec, Joint Electron Device Engineering Council, Joint Electron Tube Engineering Council, and American National Standards Institute (ANSI), EN Specifications, etc.

-
- (b) To designate a part as a standard part, the TC holder may issue a standard parts manual accepted by the competent authority of the original TC holder or may make reference in the parts catalogue to the specification to be met by the standard part. Documentation that accompanies standard parts should clearly relate to the particular parts and contain a conformity statement plus both the manufacturing and supplier source. Some materials are subject to special conditions, such as storage conditions or life limitation, etc., and this should be included in the documentation and/or the material's packaging.
- (c) CAAB Form 1 or equivalent is not normally issued and, therefore, none should be expected.

AMC1 145.A.42(a)(v) Components

Material

- (a) Consumable material is any material which is only used once, such as lubricants, cements, compounds, paints, chemical dyes and sealants, etc.
- (b) Raw material is any material that requires further work to make it into a component part of the aircraft, such as metal, plastic, wood, fabric, etc.
- (c) Material both raw and consumable should only be accepted when satisfied that it is to the required specification. To be satisfied, the material and/or its packaging should be marked with the applicable specification and, where appropriate, the batch number.
- (d) Documentation that accompanies all materials should clearly relate to the particular material and contain a conformity statement plus both the manufacturing and supplier source. Some materials are subject to special conditions, such as storage conditions or life limitation, etc., and this should be included in the documentation and/or the material's packaging.
- (e) CAAB Form 1 or equivalent should not be issued for such materials and, therefore, none should be expected. The material specification is normally identified in the (S)TC holder's data except in the case where the CAAB has agreed otherwise.

AMC1 145.A.42(b)(i) Components

Acceptance of Components for Installation

- a) The procedures for the acceptance of components, standard parts and materials should have the objective of ensuring that the components, standard parts and materials are in satisfactory condition and meet the organisation's requirements.

These procedures should be based upon incoming inspections, which include:

- (1) physical inspection of the components, standard parts and materials;
 - (2) review of the accompanying documentation and data, which should be acceptable in accordance with 145.A.42(a).
- (b) For the acceptance of components, standard parts and materials from suppliers, the above procedures should include supplier evaluation procedures.

AMC1 145.A.42(b)(iii) Components

Fabrication of Parts for Installation

- (a) The agreement of the CAAB on the fabrication of parts by the approved maintenance organisation should be formalised through the approval of a detailed procedure in the Maintenance Organisation Exposition (MOE). This AMC contains principles and conditions to be taken into account for the preparation of an acceptable procedure.
- (b) Fabrication, inspection, assembly and test should be clearly within the technical and procedural capability of the organisation.
- (c) All necessary data to fabricate the part should be approved either by competent authority of the state of design or the type certificate (TC) holder, or Part21 design organisation approval holder, or supplemental type certificate (STC) holder.
- (d) Items that are fabricated by an organisation approved under Part-145 may only be used by that organisation in the course of overhaul, maintenance, modifications, or repair of aircraft or components, performing work at its own facilities. The permission to fabricate does not constitute approval for manufacture, or to supply externally, and the parts do not qualify for CAAB Form 1 certification. This prohibition also applies to the bulk transfer of surplus inventory, in that locally fabricated parts are physically segregated and excluded from any delivery certification.
- (e) Fabrication of parts, modification kits, etc., for onward supply and/or sale may not be conducted by an organisation that is approved under Part-145

- (f) The data specified in (c) may include repair procedures that involve the fabrication of parts. Where the data on such parts is sufficient to facilitate fabrication, the parts may be fabricated by an organisation that is approved under Part-145. Care should be taken to ensure that the data include details of part numbering, dimensions, materials, processes, and any special manufacturing techniques, special raw material specification and/or incoming inspection requirement, and that the approved organisation has the necessary capability to fabricate those parts. That capability should be defined by way of exposition content. Where special processes or inspection procedures are defined in the approved data, which are not available at the organisation, the organisation cannot fabricate the part unless the TC/STC holder gives an approved alternative.
- (g) Examples of fabrication within the scope of a Part-145 approval may include but are not limited to the following:
- (1) fabrication of bushes, sleeves and shims;
 - (2) fabrication of secondary structural elements and skin panels;
 - (3) fabrication of control cables;
 - (4) fabrication of flexible and rigid pipes;
 - (5) fabrication of electrical cable looms and assemblies;
 - (6) formed or machined sheet metal panels for repairs.

All the above-mentioned fabricated parts should be in accordance with the data provided in the overhaul or repair manuals, modification schemes and service bulletins, drawings, or should be otherwise approved by the CAAB.

Note: It is not acceptable to fabricate any item to pattern unless an engineering drawing of the item is produced which includes any necessary fabrication process and which is acceptable to the CAAB.

- (h) Where a TC holder or an approved production organisation is prepared to make available complete data which is not referred to in the aircraft manuals or service bulletins but provides manufacturing drawings for items specified in parts lists, the fabrication of these items is not considered to be within the scope of an approval unless agreed otherwise by the CAAB in accordance with a procedure specified in the exposition.

(i) Inspection and identification

Any locally fabricated part should be subject to inspection before, separately, and preferably independently from any inspection of its installation. The inspection should establish full compliance with the relevant manufacturing data, and the part should be unambiguously identified as fit for use by stating conformity to the approved data. Adequate records should be maintained of all such fabrication processes including heat treatment and final inspections. All parts, except those that do not have enough space, should carry a part number, which clearly relates it to the manufacturing/inspection data. In addition to the part's number, the organisation's identity should be marked on the part for traceability purposes.

AMC1 145.A.42(c) Components

Segregation of Components

- (a) Unserviceable components should be identified and stored in a secure location that is under the control of the maintenance organisation until a decision is made on the future status of such components. The organisation that declared the component to be unserviceable may transfer its custody after identifying it as unserviceable to the aircraft owner provided that such transfer is reflected in the aircraft logbook, or engine logbook, or component logbook.
- (b) 'Secure location under the control of an approved maintenance organisation' refers to a secure location whose security is the responsibility of the approved maintenance organisation. This may include facilities that are established by the organisation at locations different from the main maintenance facilities. These locations should be identified in the relevant procedures of the organisation.
- (c) In the case of unsalvageable components, the organisation should:
- (1) retain such component in the secure location referred to in paragraph (b);
 - (2) arrange for the component to be mutilated in a manner that ensures that they are beyond economic salvage or repair before disposing it; or

- (3) mark the component indicating that it is unsalvageable, when in agreement with the component owner, the component is disposed of for legitimate nonflight uses (such as training and education aids, research and development), or for non-aviation applications, mutilation is often not appropriate. Alternatively to marking, the original part number or data plate information can be removed or a record kept of the disposal of the components.

145.A.45 Maintenance Data

- (a) The organisation shall hold and use applicable current maintenance data in the performance of maintenance, including modifications and repairs.

"Applicable" means relevant to any aircraft, component or process specified in the organisation's approval class rating schedule and in any associated capability list.

In the case of maintenance data provided by an operator or customer, the organisation shall hold such data when the work is in progress, with the exception of the need to comply with 145.A.55(c).

- (b) For the purposes of this Part, applicable maintenance data shall be any of the following:
1. Any applicable requirement, procedure, operational directive or information issued by the authority responsible for the oversight of the aircraft or component;
 2. Any applicable airworthiness directive issued by the authority responsible for the oversight of the aircraft or component;
 3. Instructions for continuing airworthiness, issued by type certificate holders, supplementary type certificate holders, any other organisation required to publish such data by Part-21 organization acceptable to the CAAB and in the case of aircraft or components from third countries the airworthiness data mandated by the authority responsible for the oversight of the aircraft or component;
 4. Any applicable standard, such as but not limited to, maintenance standard practices recognised by the Agency as a good standard for maintenance;

5. Any applicable data issued in accordance with paragraph (d).
- (c) The organisation shall establish procedures to ensure that if found, any inaccurate, incomplete or ambiguous procedure, practice, information or maintenance instruction contained in the maintenance data used by maintenance personnel is recorded and notified to the author of the maintenance data.
- (d) The organisation may only modify maintenance instructions in accordance with a procedure specified in the maintenance organisation's exposition. With respect to those changes, the organisation shall demonstrate that they result in equivalent or improved maintenance standards and shall inform the type-certificate holder of such changes. Maintenance instructions for the purposes of this paragraph means instructions on how to carry out the particular maintenance task: they exclude the engineering design of repairs and modifications.
- (e) The organisation shall provide a common work card or worksheet system to be used throughout relevant parts of the organisation. In addition, the organisation shall either transcribe accurately the maintenance data contained in paragraphs (b) and (d) onto such work cards or worksheets or make precise reference to the particular maintenance task or tasks contained in such maintenance data. Work cards and worksheets may be computer generated and held on an electronic database subject to both adequate safeguards against unauthorised alteration and a back-up electronic database which shall be updated within 24 hours of any entry made to the main electronic database. Complex maintenance tasks shall be transcribed onto the work cards or worksheets and subdivided into clear stages to ensure a record of the accomplishment of the complete maintenance task.

Where the organisation provides a maintenance service to an aircraft operator who requires their work card or worksheet system to be used then such work card or worksheet system may be used. In this case, the organisation shall establish a procedure to ensure correct completion of the aircraft operators' work cards or worksheets.

- (f) The organisation shall ensure that all applicable maintenance data is readily available for use when required by maintenance personnel.

- (g) The organisation shall establish a procedure to ensure that maintenance data it controls is kept up to date. In the case of operator/customer controlled and provided maintenance data, the organisation shall be able to show that either it has written confirmation from the operator/customer that all such maintenance data is up to date or it has work orders specifying the amendment status of the maintenance data to be used or it can show that it is on the operator/customer maintenance data amendment list.

AMC 145.A.45(b) Maintenance data

1. Except as specified in sub-paragraph 5, each maintenance organisation approved under Part-145 should hold and use the following minimum maintenance data relevant to the organisation's approval class rating. All maintenance related Implementing Rules and associated AMCs, approval specifications and Guidance Material, all applicable national maintenance requirements and notices and all applicable State of Design and CAAB airworthiness directives as well as Critical Design Configuration Control Limitations.
2. In addition to sub-paragraph 1, an organisation with an approval class rating in category A - Aircraft, should hold and use the following maintenance data where published. The appropriate sections of the operator's aircraft maintenance programme, aircraft maintenance manual, repair manual, supplementary structural inspection document, corrosion control document, service bulletins, service letters, service instructions, modification leaflets, NDT manual, parts catalogue, type certificate data sheet and any other specific document issued by the type certificate or supplementary type certificate holder as maintenance data.
3. In addition to subparagraph 1, an organisation with an approval class rating in category B — Engines/APUs, should hold and use the following maintenance data where published. The appropriate sections of the engine/APU maintenance and repair manual, service bulletins, service letters, modification leaflets, non-destructive testing (NDT) manual, parts catalogue, type certificate data sheet and any other specific document issued by the type certificate holder as maintenance data.

4. In addition to sub-paragraph 1, an organisation with an approval class rating in category C - Components other than complete engines/APUs, should hold and use the following maintenance data where published. The appropriate sections of the vendor maintenance and repair manual, service bulletins and service letters plus any document issued by the type certificate holder as maintenance data on whose product the component may be fitted when applicable.
5. Appropriate sections of the sub-paragraphs 2 to 4 additional maintenance data means in relation to the maintenance work scope at each particular maintenance facility. For example, a base maintenance facility should have almost complete set(s) of the maintenance data whereas a line maintenance facility may need only the maintenance manual and the parts catalogue.
6. An organisation only approved in class rating category D – Specialised services, should hold and use all applicable specialised service(s) process specifications.

AMC 145.A.45(c) Maintenance data

- 1 The referenced procedure should ensure that when maintenance personnel discover inaccurate, incomplete or ambiguous information in the maintenance data they should record the details. The procedure should then ensure that the Part-145 approved maintenance organisation notifies the problem to the author of the maintenance data in a timely manner. A record of such communications to the author of the maintenance data should be retained by the Part-145 approved organisation until such time as the type certificate holder has clarified the issue by e.g. amending the maintenance data.
- 2 The referenced procedure should be specified in the maintenance organisation exposition.

AMC 145.A.45(d) Maintenance data

The referenced procedure should address the need for a practical demonstration by the mechanic to the quality personnel of the proposed modified maintenance instruction. When satisfied the quality personnel should approve the modified maintenance instruction and ensure that the type certificate or supplementary type certificate holder is informed of the modified maintenance instruction. The procedure should include a paper/electronic traceability of the complete process from start to finish and ensure that the relevant maintenance instruction clearly identifies the modification. Modified maintenance instructions should only be used in the following circumstances;

-
-
- (a) Where the type certificate / supplementary type certificate holders original intent can be carried out in a more practical or more efficient manner.
 - (b) Where the type certificate / supplementary type certificate holders original intent cannot be achieved by following the maintenance instructions. For example, where a component cannot be replaced following the original maintenance instructions.
 - (c) For the use of alternative tools / equipment.

Important Note: Critical Design Configuration Control Limitations (CDCCL) are airworthiness limitations. Any modification of the maintenance instructions linked to CDCCL constitutes an aircraft modification that should be approved in accordance with a standard acceptable to the CAAB.

AMC 145.A.45(e) Maintenance data

1. The maintenance organisation should:
 - transcribe accurately the maintenance data onto such work cards or worksheets, or make precise reference to the particular maintenance task(s) contained in such maintenance data, which already identifies the task as a CDCCL where applicable.
2. Relevant parts of the organisation means with regard to aircraft base maintenance, aircraft line maintenance, engine workshops, mechanical workshops and avionic workshops. Therefore, engine workshops for example should have a common system throughout such engine workshops that may be different to that in the aircraft base maintenance.
3. The work cards should differentiate and specify, when relevant, disassembly, accomplishment of task, reassembly and testing. In the case of a lengthy maintenance task involving a succession of personnel to complete such a task, it may be necessary to use supplementary work cards or worksheets to indicate what was actually accomplished by each individual person.

AMC 145.A.45(f) Maintenance data

1. Data being made available to personnel maintaining aircraft means that the data should be available in close proximity to the aircraft being maintained for supervisors, mechanics and certifying staff to study.

2. Where computer systems are used, the number of computer terminals should be sufficient in relation to the size of the work programme to enable easy access, unless the computer system can produce paper copies. Where microfilm or microfiche readers/printers are used, a similar requirement is applicable.

AMC 145.A.45(g) Maintenance data

1. To keep data up-to-date, a procedure should be set up to monitor the amendment status of all data and maintain a check that all amendments are being received by being a subscriber to any document amendment scheme. Special attention should be given to TC related data such as certification life-limited parts, airworthiness limitations and Airworthiness Limitation Items (ALI), etc.

145.A.47 Production Planning

- (a) The organisation shall have a system appropriate to the amount and complexity of work to plan the availability of all necessary personnel, tools, equipment, material, maintenance data and facilities in order to ensure the safe completion of the maintenance work.
- (b) The planning of maintenance tasks, and the organising of shifts, shall take into account human performance limitations.
- (c) When it is required to hand over the continuation or completion of maintenance tasks for reasons of a shift or personnel changeover, relevant information shall be adequately communicated between outgoing and incoming personnel.

AMC 145.A.47(a) Production planning

1. Depending on the amount and complexity of work generally performed by the maintenance organisation, the planning system may range from a very simple procedure to a complex organisational set-up including a dedicated planning function in support of the production function.
2. For the purpose of Part-145, the production planning function includes two complementary elements:

scheduling the maintenance work ahead, to ensure that it will not adversely interfere with other work as regards the availability of all necessary personnel, tools, equipment, material, maintenance data and facilities.

during maintenance work, organising maintenance teams and shifts and provide all necessary support to ensure the completion of maintenance without undue time pressure.

3. When establishing the production planning procedure, consideration should be given to the following:

logistics,

inventory control,

square meters of accommodation,

man-hours estimation,

man-hours availability,

preparation of work,

hangar availability,

environmental conditions (access, lighting standards and cleanliness),

co-ordination with internal and external suppliers, etc.

scheduling of safety-critical tasks during periods when staff are likely to be most alert.

AMC 145.A.47(b) Production planning

Limitations of human performance, in the context of planning safety related tasks, refers to the upper and lower limits, and variations, of certain aspects of human performance (Circadian rhythm / 24 hours body cycle) which personnel should be aware of when planning work and shifts.

AMC 145.A.47(c) Production planning

The primary objective of the changeover / handover information is to ensure effective communication at the point of handing over the continuation or completion of maintenance actions. Effective task and shift handover depends on three basic elements:

- The outgoing person’s ability to understand and communicate the important elements of the job or task being passed over to the incoming person.
- The incoming person’s ability to understand and assimilate the information being provided by the outgoing person.
- A formalised process for exchanging information between outgoing and incoming persons and a planned shift overlap and a place for such exchanges to take place.

145.A.48 Performance of Maintenance

- (a) The organisation may only carry out maintenance on an aircraft or component for which it is approved when all the necessary facilities, equipment, tooling, material, maintenance data and personnel are available.
- (b) The organisation shall be responsible for the maintenance that is performed within the scope of its approval.
- (c) The organisation shall ensure that:
 - (1) after the completion of the maintenance, a general verification is carried out to ensure that the aircraft or component is clear of all tools, equipment and any extraneous parts or material, and that all access panels that were removed have been refitted;
 - (2) an error-capturing method is implemented after the performance of any critical maintenance task;
 - (3) the risk of errors during maintenance and the risk of errors being repeated in identical maintenance tasks are minimised;
 - (4) damage is assessed, and modifications and repairs are carried out using the data specified in point M.A.304 of ANO Part-M;
 - (5) the assessment of aircraft defects is carried out in accordance with point M.A.403(b) of ANO Part-M.

AMC1 145.A.48(a) Performance of maintenance

Point (a) of 145.A.48 is intended to cover the situation where the organisation may temporarily not hold all the necessary tools, equipment, material, maintenance data, etc. for an aircraft type or variant, or component specified in the organisation’s scope of work. This point means that the CAAB need not amend the approval to delete the aircraft type or variants, or component on the basis that it is a temporary situation and there is a commitment from the organisation to re-acquire tools, equipment etc. before maintenance on the related aircraft or component may recommence.

AMC1 145.A.48(c)(2) Performance of maintenance

The organisation should have a procedure to identify the error-capturing methods, the critical maintenance tasks, the training and the qualifications of staff applying error-capturing methods, and how the organisation ensures that its staff is familiar with critical maintenance tasks and error capturing methods.

AMC2 145.A.48(c)(2) Performance of maintenance**Critical Maintenance Tasks**

- (a) The procedure should ensure that the following maintenance tasks are reviewed to assess their impact on flight safety:
 - (1) tasks that may affect the control of the aircraft flight path and attitude, such as installation, rigging and adjustments of flight controls;
 - (2) aircraft stability control systems (autopilot, fuel transfer);
 - (3) tasks that may affect the propulsive force of the aircraft, including installation of aircraft engines, propellers and rotors; and
 - (4) overhaul, calibration or rigging of engines, propellers, transmissions and gearboxes.
- (b) The procedure should describe which data sources are used to identify critical maintenance tasks. Several data sources may be used, such as:
 - (1) information from the design approval holder;
 - (2) accident reports;
 - (3) investigation and follow-up of incidents;
 - (4) occurrence reporting;
 - (5) flight data analysis, where this is available from the person or organisation responsible for the aircraft continuing airworthiness;
 - (6) results of audits and independent inspections;
 - (7) monitoring schemes for normal operations, where these are available from the person or organisation responsible for the aircraft continuing airworthiness;
 - (8) feedback from training.

AMC3 145.A.48(c)(2) Performance of maintenance

Error-Capturing Methods

- (a) Error-capturing methods are those actions defined by the organisation to detect maintenance errors that are made while performing maintenance.
- (b) The organisation should ensure that the error-capturing methods are adequate for the work and the disturbance of the system. A combination of several actions (e.g. visual inspection, operational check, functional test, rigging check) may be necessary in some cases.

AMC4 145.A.48(c)(2) Performance of maintenance

Independent Inspection

Independent inspection is one possible error-capturing method.

- (a) What is an independent inspection

An independent inspection is an inspection performed by an ‘independent qualified person’ of a task carried out by an ‘authorised person’, taking into account that:

- (1) the ‘authorised person’ is the person who performs the task or supervises the task and they assume the full responsibility for the completion of the task in accordance with the applicable maintenance data;
- (2) the ‘independent qualified person’ is the person who performs the independent inspection and attests the satisfactory completion of the task and that no deficiencies have been found. The ‘independent qualified person’ does not issue a certificate of release to service, therefore they are not required to hold certification privileges;
- (3) the ‘authorised person’ issues the certificate of release to service or signs off the completion of the task after the independent inspection has been carried out satisfactorily;
- (4) the work card system used by the organisation should record the identification of both persons and the details of the independent inspection as necessary before the certificate of release to service or sign-off for the completion of the task is issued.

(b) Qualifications of persons performing independent inspections

The organisation should have procedures to demonstrate that the ‘independent qualified person’ has been trained and has gained experience in the specific inspection to be performed.

The organisation could consider making use of, for example:

- (1) staff holding a certifying staff or support staff or sign-off authorisation or equivalent necessary to release or sign off the critical maintenance task;
- (2) staff holding a certifying staff or support staff or sign-off authorisation or equivalent necessary to release or sign off similar task in a product of similar category and having received specific practical training in the task to be inspected; or
- (3) a commander holding a limited certification authorisation in accordance with 145.A.30(j)(4) and having received adequate practical training and having enough experience in the specific task to be inspected and on how to perform independent inspection.

(c) How to perform an independent inspection

An independent inspection should ensure correct assembly, locking and sense of operation.

When inspecting control systems that have undergone maintenance, the independent qualified person should consider the following points independently:

- (1) all those parts of the system that have actually been disconnected or disturbed should be inspected for correct assembly and locking;
- (2) the system as a whole should be inspected for full and free movement over the complete range;
- (3) cables should be tensioned correctly with adequate clearance at secondary stops;
- (4) the operation of the control system as a whole should be observed to ensure that the controls are operating in the correct sense;
- (5) if different control systems are interconnected so that they affect each other, all the interactions should be checked through the full range of the applicable controls; and

- (6) software that is part of the critical maintenance task should be checked, for example: version, compatibility with aircraft configuration.
- (d) What to do in unforeseen cases when only one person is available

Reinspection:

- (1) Reinspection is an error-capturing method subject to the same conditions as an independent inspection is, except that the ‘authorised person’ performing the maintenance task is also acting as ‘independent qualified person’ and performs the inspection.
- (2) Reinspection, as an error-capturing method, should only be performed in unforeseen circumstances when only one person is available to carry out the task and perform the independent inspection. The circumstances cannot be considered unforeseen if the person or organisation has not assigned a suitable ‘independent qualified person’ to that particular line station or shift.
- (3) The certificate of release to service is issued after the task has been performed by the ‘authorised person’ and the reinspection has been carried out satisfactorily. The work card system used by the organisation should record the identification and the details of the reinspection before the certificate of release to service for the task is issued.

AMC1 145.A.48(c)(3) Performance of maintenance

The procedures should be aimed at:

- (a) minimising errors and preventing omissions. Therefore, the procedures should specify:
- (1) that every maintenance task is signed off only after completion;
- (2) how the grouping of tasks for the purpose of sign-off allows critical steps to be clearly identified; and
- (3) that work performed by personnel under supervision (i.e. temporary staff, trainees) is checked and signed off by an authorised person;

-
- (b) minimising the possibility of an error being repeated in identical tasks and, therefore, compromising more than one system or function. Thus, the procedures should ensure that no person is required to perform a maintenance task involving removal/installation or assembly/disassembly of several components of the same type fitted to more than one system, a failure of which could have an impact on safety, on the same aircraft or component during a particular maintenance check. However, in unforeseen circumstances when only one person is available, the organisation may make use of reinspection as described in point (d) of AMC4 145.A.48(c)(2).

145.A.50 Certification of Maintenance

- (a) A certificate of release to service shall be issued by appropriately authorised certifying staff on behalf of the organisation when it has been verified that all maintenance ordered has been properly carried out by the organisation in accordance with the procedures specified in point 145.A.70, taking into account the availability and use of the maintenance data specified in point 145.A.45 and that there are no non-compliances which are known to endanger flight safety.
- (b) A certificate of release to service shall be issued before flight at the completion of any maintenance.
- (c) New defects or incomplete maintenance work orders identified during the above maintenance shall be brought to the attention of the aircraft operator for the specific purpose of obtaining agreement to rectify such defects or completing the missing elements of the maintenance work order. In the case where the aircraft operator declines to have such maintenance carried out under this paragraph, paragraph (e) is applicable.
- (d) A certificate of release to service shall be issued at the completion of any maintenance on a component whilst off the aircraft. The authorised release certificate CAAB Form 1 referred to in Appendix I of this Part constitutes the component certificate of release to service. When an organisation maintains a component for its own use, a CAAB Form 1 may not be necessary depending upon the organisation's internal release procedures defined in the exposition.
- (e) By derogation to paragraph (a), when the organisation is unable to complete all maintenance ordered, it may issue a certificate of release to service within the approved aircraft limitations. The organisation shall enter such fact in the aircraft certificate of release to service before the issue of such certificate.

- (f) By derogation to paragraph (a) and 145.A.42, when an aircraft is grounded at a location other than the main line station or main maintenance base due to the non-availability of a component with the appropriate release certificate, it is permissible to temporarily fit a component without the appropriate release certificate for a maximum of 30 flight hours or until the aircraft first returns to the main line station or main maintenance base, whichever is the sooner, subject to the aircraft operator agreement and said component having a suitable release certificate but otherwise in compliance with all applicable maintenance and operational requirements. Such components shall be removed by the above prescribed time limit unless an appropriate release certificate has been obtained in the meantime under paragraph (a) and 145.A.42.

AMC 145.A.50(a) Certification of maintenance

'Endangers the flight safety' means any instances where safe operation could not be assured or which could lead to an unsafe condition. It typically includes, but is not limited to, significant cracking, deformation, corrosion or failure of primary structure, any evidence of burning, electrical arcing, significant hydraulic fluid or fuel leakage and any emergency system or total system failure. An airworthiness directive overdue for compliance is also considered a hazard to flight safety.

AMC 145.A.50(b) Certification of maintenance

1. The certificate of release to service should contain the following statement:
'Certifies that the work specified, except as otherwise specified, was carried out in accordance with Part-145 and in respect to that work the aircraft/aircraft component is considered ready for release to service'.
Reference should also be made to the CAAB Part-145 approval number.
2. It is acceptable to use an alternate abbreviated certificate of release to service consisting of the following statement 'Part-145 release to service' instead of the full certification statement specified in paragraph 1. When the alternate abbreviated certificate of release to service is used, the introductory section of the technical log should include an example of the full certification statement from paragraph 1.
3. The certificate of release to service should relate to the task specified in the (S)TC holder's or operator's instructions or the aircraft maintenance programme which itself may cross-refer to maintenance data.

4. The date such maintenance was carried out should include when the maintenance took place relative to any life or overhaul limitation in terms of date/flying hours/cycles/landings etc., as appropriate.
5. When extensive maintenance has been carried out, it is acceptable for the certificate of release to service to summarise the maintenance as long as there is a unique cross-reference to the work package containing full details of maintenance carried out. Dimensional information should be retained in the work-pack record.

AMC No 1 to 145.A.50(d) Certification of maintenance

The purpose of the certificate is to release assemblies/items/components/parts (hereafter referred to as ‘item(s)’) after maintenance and to release maintenance work carried out on such items under the approval of the CAAB and to allow items removed from one aircraft/aircraft component to be fitted to another aircraft/aircraft component.

The certificate is to be used for export/import purposes, as well as for domestic purposes, and serves as an official certificate for items from the manufacturer/maintenance organisation to users.

It can only be issued by organisations approved by the CAAB within the scope of the approval.

The certificate may be used as a rotatable tag by utilising the available space on the reverse side of the certificate for any additional information and dispatching the item with two copies of the certificate so that one copy may be eventually returned with the item to the maintenance organisation. The alternative solution is to use existing rotatable tags and also supply a copy of the certificate.

A certificate should not be issued for any item when it is known that the item is unserviceable except in the case of an item undergoing a series of maintenance processes at several maintenance organisations approved under Part-145 and the item needs a certificate for the previous maintenance process carried out for the next maintenance organisation approved under Part-145 to accept the item for subsequent maintenance processes. In such a case, a clear statement of limitation should be endorsed in Block 12.

AMC No 2 to 145.A.50(d) Certification of maintenance

1. A component which has been maintained off the aircraft needs the issuance of a certificate of release to service for such maintenance and another certificate of release to service in regard to being installed properly on the aircraft when such action occurs.

When an organisation maintains a component for use by the same organisation, a CAAB Form 1 may not be necessary depending upon the organisation's internal release procedures defined in the maintenance organisation exposition.

2. In the case of the issue of a CAAB Form 1 for components in storage before Part-145 and Part-21 became effective and not released on an CAAB Form 1 or equivalent in accordance with 145.A.42(a) or removed serviceable from a serviceable aircraft or an aircraft which has been withdrawn from service the following applies:

- 2.1. A CAAB Form 1 may be issued for an aircraft component which has been:

Maintained before Part-145 became effective or manufactured before Part-21 became effective.

Used on an aircraft and removed in a serviceable condition. Examples include leased and loaned aircraft components.

Removed from aircraft which have been withdrawn from service, or from aircraft which have been involved in abnormal occurrences such as accidents, incidents, heavy landings or lightning strikes.

Maintained by an unapproved organisation.

- 2.2. An appropriately rated maintenance organisation approved under Part-145 may issue a CAAB Form 1 as detailed in this AMC subparagraph 2.5 to 2.9, as appropriate, in accordance with procedures detailed in the exposition as approved by the CAAB. The appropriately rated organisation is responsible for ensuring that all reasonable measures have been taken to ensure that only approved and serviceable aircraft components are issued a CAAB Form 1 under this paragraph.

- 2.3. For the purposes of this AMC No 2 only, appropriately rated means an organisation with an approval class rating for the type of component or for the product in which it may be installed.

2.4. A CAAB Form 1 issued in accordance with this paragraph 2 should be issued by signing in block 14b and stating 'Inspected' in block 11. In addition, block 12 should specify:

2.4.1. When the last maintenance was carried out and by whom.

2.4.2. If the component is unused, when the component was manufactured and by whom with a cross-reference to any original documentation which should be included with the Form.

2.4.3. A list of all airworthiness directives, repairs and modifications known to have been incorporated. If no airworthiness directives or repairs or modifications are known to be incorporated, then this should be so stated.

2.4.4. Detail of life used for service life-limited parts being any combination of fatigue, overhaul or storage life.

2.4.5. For any aircraft component having its own maintenance history record, reference to the particular maintenance history record as long as the record contains the details that would otherwise be required in block 12. The maintenance history record and acceptance test report or statement, if applicable, should be attached to the CAAB Form 1.

2.5. New/unused aircraft components

2.5.1 Any unused aircraft component in storage without a CAAB Form 1 up to the effective date(s) for Part-21 that was manufactured by an organisation acceptable to the CAAB at that time may be issued with a CAAB Form 1 by an appropriately rated maintenance organisation approved under Part-145. The CAAB Form 1 should be issued in accordance with the following subparagraphs which should be included in a procedure within the maintenance organisation manual.

Note 1: It should be understood that the release of a stored but unused aircraft component in accordance with this paragraph represents a maintenance release under Part-145 and not a production release under Part-21.

- (a) An acceptance test report or statement should be available for all used and unused aircraft components that are subjected to acceptance testing after manufacturing or maintenance as appropriate.
- (b) The aircraft component should be inspected for compliance with the manufacturer's instructions and limitations for storage and condition including any requirement for limited storage life, inhibitors, controlled climate and special storage containers. In addition or in the absence of specific storage instructions the aircraft component should be inspected for damage, corrosion and leakage to ensure good condition.
- (c) The storage life used of any storage life-limited parts should be established.

2.5.2. If it is not possible to establish satisfactory compliance with all applicable conditions specified in subparagraph 2.5.1 (a) to (c) inclusive, the aircraft component should be disassembled by an appropriately rated organisation and subjected to a check for incorporated airworthiness directives, repairs and modifications and inspected/tested in accordance with the maintenance data to establish satisfactory condition and, if relevant, all seals, lubricants and life-limited parts should be replaced. Upon satisfactory completion after reassembly, a CAAB Form 1 may be issued stating what was carried out and the reference of the maintenance data included.

2.6. Used aircraft components removed from a serviceable aircraft

2.6.1. Serviceable aircraft components removed from a CAAB registered aircraft may be issued with a CAAB Form 1 by an appropriately rated organisation subject to compliance with this subparagraph.

- (a) The organisation should ensure that the component was removed from the aircraft by an appropriately qualified person.
- (b) The aircraft component may only be deemed serviceable if the last flight operation with the component fitted revealed no faults on that component/related system.

- (c) The aircraft component should be inspected for satisfactory condition including in particular damage, corrosion or leakage and compliance with any additional maintenance data.
 - (d) The aircraft record should be researched for any unusual events that could affect the serviceability of the aircraft component such as involvement in accidents, incidents, heavy landings or lightning strikes. Under no circumstances may a CAAB Form 1 be issued in accordance with this paragraph 2.6 if it is suspected that the aircraft component has been subjected to extremes of stress, temperatures or immersion which could affect its operation.
 - (e) A maintenance history record should be available for all used serialised aircraft components.
 - (f) Compliance with known modifications and repairs should be established.
 - (g) The flight hours/cycles/landings as applicable of any service life-limited parts including time since overhaul should be established.
 - (h) Compliance with known applicable airworthiness directives should be established.
 - (i) Subject to satisfactory compliance with this subparagraph 2.6.1, a CAAB Form 1 may be issued and should contain the information as specified in paragraph 2.4 including the aircraft from which the aircraft component was removed.
- 2.6.2. Serviceable aircraft components removed from a non CAAB registered aircraft may only be issued with a CAAB Form 1 if the components are leased or loaned from the maintenance organisation approved under Part-145 who retains control of the airworthiness status of the components. A CAAB Form 1 may be issued and should contain the information as specified in paragraph 2.4 including the aircraft from which the aircraft component was removed.

2.7. Used aircraft components removed from an aircraft withdrawn from service. Serviceable aircraft components removed from a Bangladeshi registered aircraft withdrawn from service may be issued with a CAAB Form 1 by a maintenance organisation approved under Part-145 subject to compliance with this subparagraph.

- (a) Aircraft withdrawn from service are sometimes dismantled for spares. This is considered to be a maintenance activity and should be accomplished under the control of an organisation approved under Part-145, employing procedures approved by the CAAB.
- (b) To be eligible for installation, components removed from such aircraft may be issued with a CAAB Form 1 by an appropriately rated organisation following a satisfactory assessment.
- (c) As a minimum, the assessment will need to satisfy the standards set out in paragraphs 2.5 and 2.6 as appropriate. This should, where known, include the possible need for the alignment of scheduled maintenance that may be necessary to comply with the maintenance programme applicable to the aircraft on which the component is to be installed.
- (d) Irrespective of whether the aircraft holds a certificate of airworthiness or not, the organisation responsible for certifying any removed component should ensure that the manner in which the components were removed and stored are compatible with the standards required by Part-145.
- (e) A structured plan should be formulated to control the aircraft disassembly process. The disassembly is to be carried out by an appropriately rated organisation under the supervision of certifying staff who will ensure that the aircraft components are removed and documented in a structured manner in accordance with the appropriate maintenance data and disassembly plan.

-
- (f) All recorded aircraft defects should be reviewed and the possible effects these may have on both normal and standby functions of removed components are to be considered.
 - (g) Dedicated control documentation is to be used as detailed by the disassembly plan, to facilitate the recording of all maintenance actions and component removals performed during the disassembly process. Components found to be unserviceable are to be identified as such and quarantined pending a decision on the actions to be taken. Records of the maintenance accomplished to establish serviceability are to form part of the component maintenance history.
 - (h) Suitable Part-145 facilities for the removal and storage of removed components are to be used which include suitable environmental conditions, lighting, access equipment, aircraft tooling and storage facilities for the work to be undertaken. While it may be acceptable for components to be removed, given local environmental conditions, without the benefit of an enclosed facility, subsequent disassembly (if required) and storage of the components should be in accordance with the manufacturer's recommendations.
- 2.8. Used aircraft components maintained by organisations not approved in accordance with Part-145. For used components maintained by a maintenance organisation not approved under Part-145, due care should be taken before acceptance of such components. In such cases an appropriately rated maintenance organisation approved under Part-145 should establish satisfactory conditions by:
- (a) dismantling the component for sufficient inspection in accordance with the appropriate maintenance data;
 - (b) replacing all service life-limit components when no satisfactory evidence of life used is available and/or the components are in an unsatisfactory condition;
 - (c) reassembling and testing as necessary the component;
 - (d) completing all certification requirements as specified in 145.A.50.

2.9. Used aircraft components removed from an aircraft involved in an accident or incident. Such components should only be issued with a CAAB Form 1 when processed in accordance with paragraph 2.7 and a specific work order including all additional necessary tests and inspections deemed necessary by the accident or incident. Such a work order may require input from the TC holder or original manufacturer as appropriate. This work order should be referenced in block 12.

AMC 145.A.50(e) Certification of maintenance

1. Being unable to establish full compliance with sub-paragraph Part-145.A.50(a) means that the maintenance required by the aircraft operator could not be completed due either to running out of available aircraft maintenance downtime for the scheduled check or by virtue of the condition of the aircraft requiring additional maintenance downtime.
2. The aircraft operator is responsible for ensuring that all required maintenance has been carried out before flight and therefore 145.A.50(e) requires such operator to be informed in the case where full compliance with 145.A.50(a) cannot be achieved within the operator's limitations. If the operator agrees to the deferment of full compliance, then the certificate of release to service may be issued subject to details of the deferment, including the operator's authority, being endorsed on the certificate.

Note: Whether or not the aircraft operator does have the authority to defer maintenance is an issue between the aircraft operator and the CAAB. In case of doubt concerning such a decision of the operator, the approved maintenance organisation should inform CAAB on such doubt, before issuing the certificate of release to service. This will allow the CAAB to investigate the matter as appropriate.

3. The procedure should draw attention to the fact that 145.A.50 (a) does not normally permit the issue of a certificate of release to service in the case of non-compliance and should state what action the mechanic, supervisor and certifying staff should take to bring the matter to the attention of the relevant department or person responsible for technical co-ordination with the aircraft operator so that the issue may be discussed and resolved with the aircraft operator. In addition, the appropriate person(s) as specified in 145.A.30(b) should be kept informed in writing of such possible non-compliance situations and this should be included in the procedure.

AMC 145.A.50(f) Certification of maintenance

1. Suitable release certificate means a certificate which clearly states that the aircraft component is serviceable; that clearly specifies the organisation releasing said component together with details of the authority under whose approval the organisation works including the approval or authorisation reference.
2. Compliance with all other Part-145 and operator requirements means making an appropriate entry in the aircraft technical log, checking for compliance with type design standards, modifications, repairs, airworthiness directives, life limitations and condition of the aircraft component plus information on where, when and why the aircraft was grounded.

145.A.55 Maintenance Records

- (a) The organisation shall record all details of maintenance work carried out. As a minimum, the organisation shall retain records necessary to prove that all requirements have been met for issuance of the certificate of release to service, including subcontractor's release documents.
- (b) The organisation shall provide a copy of each certificate of release to service to the aircraft operator, together with a copy of any specific repair/modification data used for repairs/modifications carried out.
- (c) The organisation shall retain a copy of all detailed maintenance records and any associated maintenance data for three years from the date the aircraft or component to which the work relates was released from the organisation.
 1. The records under this paragraph shall be stored in a manner that ensures protection from damage, alteration and theft.
 2. Computer backup discs, tapes etc. shall be stored in a different location from that containing the working discs, tapes etc., in an environment that ensures they remain in good condition.
 3. Where an organisation approved under this Part terminates its operation, all retained maintenance records covering the last two years shall be distributed to the last owner or customer of the respective aircraft or component or shall be stored as specified by the CAAB.

AMC 145.A.55(c) Maintenance records

Associated maintenance data is specific information such as repair and modification data. This does not necessarily require the retention of all Aircraft Maintenance Manual, Component Maintenance Manual, IPC etc. issued by the TC holder or STC holder. Maintenance records should refer to the revision status of the data used.

145.A.60 Occurrence Reporting

- (a) The organisation shall report to the CAAB, the state of registry and the organisation responsible for the design of the aircraft, modification (if applicable) or component any condition of the aircraft or component identified by the organisation that has resulted or may result in an unsafe condition that hazards seriously the flight safety.
- (b) The organisation shall establish an internal occurrence reporting system as detailed in the exposition to enable the collection and evaluation of such reports, including the assessment and extraction of those occurrences to be reported under paragraph (a). This procedure shall identify adverse trends, corrective actions taken or to be taken by the organisation to address deficiencies and include evaluation of all known relevant information relating to such occurrences and a method to circulate the information as necessary.
- (c) The organisation shall make such reports in a form and manner established by the CAAB and ensure that they contain all pertinent information about the condition and evaluation results known to the organisation.
- (d) Where the organisation is contracted by a commercial operator to carry out maintenance, the organisation shall also report to the operator any such condition affecting the operator's aircraft or component.
- (e) The organisation shall produce and submit such reports as soon as practicable but in any case within 72 hours of the organisation identifying the condition to which the report relates.

AMC 145.A.60(a) Occurrence reporting

CAAB Guidance Material GM 20-8 provides further guidance on occurrence reporting.

AMC 145.A.60(b) Occurrence reporting

1. The aim of occurrence reporting is to identify the factors contributing to incidents, and to make the system resistant to similar errors.
2. An occurrence reporting system should enable and encourage free and frank reporting of any (potentially) safety related occurrence. This will be facilitated by the establishment of a just culture. An organisation should ensure that personnel are not inappropriately punished for reporting or co-operating with occurrence investigations.
3. The internal reporting process should be closed-loop, ensuring that actions are taken internally to address safety hazards.
4. Feedback to reportees, both on an individual and more general basis, is important to ensure their continued support for the scheme.

145.A.65 Safety and Quality Policy, Maintenance Procedures and Quality System

- (a) The organisation shall establish a safety and quality policy for the organisation to be included in the exposition under 145.A.70.
- (b) The organisation shall establish procedures agreed by the CAAB taking into account human factors and human performance to ensure good maintenance practices and compliance with this Part which shall include a clear work order or contract such that aircraft and components may be released to service in accordance with point 145.A.50.
 1. The maintenance procedures under this paragraph apply to points 145.A.25 to 145.A.95.
 2. The maintenance procedures established or to be established by the organisation under this paragraph shall cover all aspects of carrying out the maintenance activity, including the provision and control of specialised services and lay down the standards to which the organisation intends to work.
 3. With regard to aircraft line and base maintenance, the organisation shall establish procedures to minimise the risk of multiple errors and capture errors on critical systems, and to ensure that no person is required to carry out and inspect in relation to a maintenance task

- involving some element of disassembly/ reassembly of several components of the same type fitted to more than one system on the same aircraft during a particular maintenance check. However, when only one person is available to carry out these tasks then the organisation's work card or worksheet shall include an additional stage for re-inspection of the work by this person after completion of all the same tasks.
4. Maintenance procedures shall be established to ensure that damage is assessed and modifications and repairs are carried out using data approved by the CAAB or by a design organisation acceptable to the CAAB as appropriate.
- (c) The organisation shall establish a quality system that includes the following:
1. Independent audits in order to monitor compliance with required aircraft/aircraft component standards and adequacy of the procedures to ensure that such procedures invoke good maintenance practices and airworthy aircraft/aircraft components. In the smallest organisations the independent audit part of the quality system may be contracted to another organisation approved under this Part-145 or a person with appropriate technical knowledge and proven satisfactory audit experience; and
 2. A quality feedback reporting system to the person or group of persons specified in 145.A.30(b) and ultimately to the accountable manager that ensures proper and timely corrective action is taken in response to reports resulting from the independent audits established to meet paragraph (1).
- (d) The organization shall establish a Safety Management System (SMS) that:
- (1) Shall achieve the following objectives as a minimum:
 - (i) Identifies safety hazards;
 - (ii) Assesses the impact of these safety hazards and mitigates risks;
 - (iii) Ensures that remedial action necessary to maintain an acceptable level of safety is implemented;

- (iv) Provides for continuous monitoring and regular assessment of the safety level achieved; and
 - (v) Aims to make continuous improvement to the overall level of safety.
- (2) Shall meet the requirements contained in Appendix V to this Part; and
- (3) Shall be approved by the CAAB.

AMC 145.A.65(a) Safety and quality policy, maintenance procedures and quality system

The safety and quality policy should as a minimum include a statement committing the organisation to:

- Recognise safety as a prime consideration at all times.
- Apply Human factors principles.
- Encourage personnel to report maintenance related errors/incidents.
- Recognise that compliance with procedures, quality standards, safety standards and regulations is the duty of all personnel.
- Recognise the need for all personnel to cooperate with the quality auditors.

AMC 145.A.65(b) Safety and quality policy, maintenance procedures and quality system

1. Maintenance procedures should be held current such that they reflect best practice within the organisation. It is the responsibility of all organisation's employees to report any differences via their organisation's internal occurrence reporting mechanisms.
2. All procedures, and changes to those procedures, should be verified and validated before use where practicable.
3. All technical procedures should be designed and presented in accordance with good human factors principles.

AMC 145.A.65(b)(2) Safety and quality policy, maintenance procedures and quality system

Specialised services include any specialised activity, such as, but not limited to non-destructive testing requiring particular skills and/or qualification. 145.A.30 (f) covers the qualification of personnel but, in addition, there is a need to establish maintenance procedures that cover the control of any specialised process.

AMC 145.A.65(b)(3) Safety and quality policy, maintenance procedures and quality system

1. The purpose of this procedure is to minimise the rare possibility of an error being repeated whereby the identical aircraft components are not reassembled thereby compromising more than one system. One example is the remote possibility of failure to reinstall engine gearbox access covers or oil filler caps on all engines of a multi-engined aircraft resulting in major oil loss from all engines.

Another example is the case of removal and refitment of oil filler caps, which should require a re-inspection of all oil filler caps after the last oil filler cap has supposedly been refitted.

2. Procedures should be established to detect and rectify maintenance errors that could, as minimum, result in a failure, malfunction, or defect endangering the safe operation of the aircraft if not performed properly. The procedure should identify the method for capturing errors, and the maintenance tasks or processes concerned.

In order to determine the work items to be considered, the following maintenance tasks should primarily be reviewed to assess their impact on safety:

Installation, rigging and adjustments of flight controls,

Installation of aircraft engines, propellers and rotors,

Overhaul, calibration or rigging of components such as engines, propellers, transmissions and gearboxes but additional information should also be processed, such as:

Previous experiences of maintenance errors, depending on the consequence of the failure,

Information arising from the ‘occurrence reporting system’ required by 145.A.60,

CAAB requirements for error capturing, if applicable.

3. In order to prevent omissions, every maintenance task or group of tasks should be signed-off. To ensure the task or group of tasks is completed it should only be signed-off after completion. Work by unauthorised personnel (i.e. temporary staff, trainee,..) should be checked by authorised personnel before they sign-off. The grouping of tasks for the purpose of signing-off should allow critical steps to be clearly identified

Note: A “sign-off” is a statement by the competent person performing or supervising the work, that the task or group of tasks has been correctly performed. A sign-off relates to one step in the maintenance process and is therefore different to the release to service of the aircraft. “Authorised personnel” means personnel formally authorised by the maintenance organisation approved under Part-145 to sign-off tasks. “Authorised personnel” are not necessarily “certifying staff”.

4. The maintenance organisation should ensure that when carrying out a modification, repair or maintenance, Critical Design Configuration Control Limitations are not compromised; this will require the development of appropriate procedures where necessary by the maintenance organisation. The maintenance organisation should pay particular attention to possible adverse effects of any wiring change to the aircraft, even a change not specifically associated with the fuel tank system. For example, it should be common practice to identify segregation of fuel gauging system wiring as a Critical Design Configuration Control Limitation.

Maintenance organisations can prevent adverse effects associated with wiring changes by standardising maintenance practices through training, rather than by periodic inspection. Training should be provided to end indiscriminate routing and splicing of wire and to provide comprehensive knowledge of critical design features of fuel tank systems that would be controlled by a Critical Design Configuration Control Limitation.

Guidance is provided for training to maintenance organisation personnel in Appendix IV to AMC to Part-145.

The maintenance of ignition prevention features is necessary for the inherent safety and reliability of an aircraft's fuel tank system. The aircraft cannot be operated indefinitely with the failure of an ignition prevention feature. The failure will have a direct adverse effect on operational safety. It could prevent the continued safe flight and landing of the aircraft or cause serious or fatal injury to the occupants. The fuel system review required will identify ignition prevention features of the design. The failure of any of these features may not immediately result in an unsafe condition, but it may warrant certain maintenance to support continued airworthiness.

AMC 145.A.65(c)(1) Safety and quality policy, maintenance procedures and quality system

1. The primary objectives of the quality system are to enable the organisation to ensure that it can deliver a safe product and that organisation remains in compliance with the requirements.
2. An essential element of the quality system is the independent audit
3. The independent audit is an objective process of routine sample checks of all aspects of the organisation's ability to carry out all maintenance to the required standards and includes some product sampling as this is the end result of the maintenance process. It represents an objective overview of the complete maintenance related activities and is intended to complement the 145.A.50 (a) requirement for certifying staff to be satisfied that all required maintenance has been properly carried out before issue of the certificate of release to service. Independent audits should include a percentage of random audits carried out on a sample basis when maintenance is being carried out. This means some audits during the night for those organisations that work at night.
4. Except as specified in sub-paragraphs 7 and 9, the independent audit should ensure that all aspects of Part-145 compliance are checked every 12 months and may be carried out as a complete single exercise or subdivided over the 12-month period in accordance with a scheduled plan. The independent audit does not require each procedure to be checked against each product line when it can be shown that the particular procedure is common to more

than one product line and the procedure has been checked every 12 months without resultant findings. Where findings have been identified, the particular procedure should be rechecked against other product lines until the findings have been rectified after which the independent audit procedure may revert back to 12 monthly for the particular procedure.

5. Except as specified otherwise in subparagraphs 7, the independent audit should sample check one product on each product line every 12 months as a demonstration of the effectiveness of maintenance procedures compliance. It is recommended that procedures and product audits be combined by selecting a specific product example, such as an aircraft or engine or instrument and sample checking all the procedures and requirements associated with the specific product example to ensure that the end result should be an airworthy product.

For the purpose of the independent audit, a product line includes any product under an Appendix II approval class rating as specified in the approval schedule issued to the particular organisation.

It therefore follows for example that a maintenance organisation approved under Part-145 with a capability to maintain aircraft, repair engines, brakes and autopilots would need to carry out four complete audit sample checks each year except as specified otherwise in subparagraphs 5, 7 or 9.

6. The sample check of a product means to witness any relevant testing and visually inspect the product and associated documentation. The sample check should not involve repeat disassembly or testing unless the sample check identifies findings requiring such action.
7. Except as specified otherwise in sub-paragraph 9, where the smallest organisation, that is an organisation with a maximum of 10 personnel actively engaged in maintenance, chooses to contract the independent audit element of the quality system in accordance with 145.A.65 (c)(1) it is conditional on the audit being carried out twice in every 12 month period.
8. Except as specified otherwise in sub-paragraph 9, where the organisation has line stations listed as per 145.A.75 (d) the quality system should describe how these are integrated into the system and include a plan to audit each listed line station at a frequency consistent with the extent of flight activity at the particular line station. Except as specified otherwise in sub-paragraph 9 the maximum period between audits of a particular line station should not exceed 24 months.

9. Except as specified otherwise in sub-paragraph 5, the CAAB may agree to increase any of the audit time periods specified in this AMC 145.A.65 (c)(1) by up to 100% provided that there are no safety related findings and subject to being satisfied that the organisation has a good record of rectifying findings in a timely manner.
10. A report should be raised each time an audit is carried out describing what was checked and the resulting findings against applicable requirements, procedures and products.
11. The independence of the audit should be established by always ensuring that audits are carried out by personnel not responsible for the function, procedure or products being checked. It therefore follows that a large maintenance organisation approved under Part-145, being an organisation with more than about 500 maintenance staff should have a dedicated quality audit group whose sole function is to conduct audits, raise finding reports and follow up to check that findings are being rectified. For the medium sized maintenance organisation approved under Part-145, being an organisation with less than about 500 maintenance staff, it is acceptable to use competent personnel from one section/department not responsible for the production function, procedure or product to audit the section/department that is responsible subject to the overall planning and implementation being under the control of the quality manager. Organisations with a maximum of 10 maintenance staff actively engaged in carrying out maintenance may contract the independent audit element of the quality system to another organisation or a qualified and competent person approved by the CAAB.

AMC 145.A.65(c)(2) Safety and quality policy, maintenance procedures and quality system

1. An essential element of the quality system is the quality feedback system.
2. The quality feedback system may not be contracted to outside persons. The principle function of the quality feedback system is to ensure that all findings resulting from the independent quality audits of the organisation are properly investigated and corrected in a timely manner and to enable the accountable manager to be kept informed of any safety issues and the extent of compliance with Part-145.

3. The independent quality audit reports referenced in AMC 145.A.65(c) (1) sub-paragraph 10 should be sent to the relevant department(s) for rectification action giving target rectification dates. Rectification dates should be discussed with such department(s) before the quality department or nominated quality auditor confirms such dates in the report. The relevant department(s) are required by 145.A.65(c) (2) to rectify findings and inform the quality department or nominated quality auditor of such rectification.
4. The accountable manager should hold regular meetings with staff to check progress on rectification except that in the large organisations such meetings may be delegated on a day to day basis to the quality manager subject to the accountable manager meeting at least twice per year with the senior staff involved to review the overall performance and receiving at least a half yearly summary report on findings of non-compliance.
5. All records pertaining to the independent quality audit and the quality feedback system should be retained for at least 2 years after the date of clearance of the finding to which they refer or for such periods as to support changes to the AMC 145.A.65(c)(1) sub-paragraph 9 audit time periods, whichever is the longer.

145.A.70 Maintenance Organisation Exposition

- (a) "Maintenance organisation exposition" means the document or documents that contain the material specifying the scope of work deemed to constitute approval and showing how the organisation intends to comply with this Part.

The organisation shall provide the CAAB with a maintenance organisation exposition, containing the following information:

1. A statement signed by the accountable manager confirming that the maintenance organisation exposition and any referenced associated manuals define the organisation's compliance with this Part and will be complied with at all times. When the accountable manager is not the chief executive officer of the organisation then such chief executive officer shall countersign the statement;
2. the organisation's safety and quality policy as specified by 145.A.65;
3. the title(s) and name(s) of the persons nominated under 145.A.30(b);
4. the duties and responsibilities of the persons nominated under 145.A.30(b), including matters on which they may deal directly with the CAAB on behalf of the organisation;

5. an organisation chart showing associated chains of responsibility between the persons nominated under 145.A.30(b);
 6. a list of certifying staff and support staff;
 7. a general description of manpower resources;
 8. a general description of the facilities located at each address specified in the organisation's approval certificate;
 9. a specification of the organisation's scope of work relevant to the extent of approval;
 10. the notification procedure of 145.A.85 for organisation changes;
 11. the maintenance organisation exposition amendment procedure;
 12. the procedures and quality system established by the organisation under 145.A.25 to 145.A.90;
 13. a list of commercial operators, where applicable, to which the organisation provides an aircraft maintenance service;
 14. a list of subcontracted organisations, where applicable, as specified in 145.A.75(b);
 15. a list of line stations, where applicable, as specified in 145.A.75(d);
 16. a list of contracted organisations, where applicable.
- (b) The exposition shall be amended as necessary to remain an up-to-date description of the organisation. The exposition and any subsequent amendment shall be approved by the CAAB.
- (c) Notwithstanding paragraph (b) minor amendments to the exposition may be approved through an exposition procedure (hereinafter called indirect approval).
- (d) The exposition shall refer to the Safety Management System Manual (SMSM).

AMC 145.A.70(a) Maintenance organisation exposition

The following information should be included in the maintenance organisation exposition:

The information specified in 145.A.70 (a) subparagraphs (6) and (12) to (16) inclusive, whilst a part of the maintenance organisation exposition, may be kept as separate documents or on separate electronic data files subject to the management part of said exposition containing a clear cross-reference to such documents or electronic data files.

The exposition should contain the information, as applicable, specified in this AMC. The information may be presented in any subject order as long as all applicable subjects are covered. Where an organisation uses a different format, for example, to allow the exposition to serve for more than one approval, then the exposition should contain a cross-reference Annex using this list as an index with an explanation as to where the subject matter can be found in the exposition.

The exposition should contain information, as applicable, on how the maintenance organisation complies with Critical Design Configuration Control Limitations' (CDCCL) instructions.

Small maintenance organisations may combine the various items to form a simple exposition more relevant to their needs.

The operator may use electronic data processing (EDP) for publication of the maintenance organisation exposition. The maintenance organisation exposition should be made available to the CAAB in a form acceptable to the CAAB. Attention should be paid to the compatibility of EDP publication systems with the necessary dissemination of the maintenance organisation exposition, both internally and externally.

PART 0 GENERAL ORGANISATION

This section is reserved for those maintenance organisations approved under Part-145 who are also operators within the CAAB territory.

PART 1 MANAGEMENT

- 1.1 Corporate commitment by the accountable manager
- 1.2 Safety and quality policy
- 1.3 Management personnel
- 1.4 Duties and responsibilities of the management personnel
- 1.5 Management organisation chart

- 1.6 List of certifying staff and support staff
- 1.7 Manpower resources
- 1.8 General description of the facilities at each address intended to be approved
- 1.9 Organisations intended scope of work
- 1.10 Notification procedure to the CAAB regarding changes to the organisation's activities/approval/location/personnel
- 1.11 Exposition amendment procedures including, if applicable, delegated procedures

PART 2 MAINTENANCE PROCEDURES

- 2.1 Supplier evaluation and subcontract control procedure
- 2.2 Acceptance/inspection of aircraft components and material from outside contractors
- 2.3 Storage, tagging and release of aircraft components and material to aircraft maintenance
- 2.4 Acceptance of tools and equipment
- 2.5 Calibration of tools and equipment
- 2.6 Use of tooling and equipment by staff (including alternate tools)
- 2.7 Cleanliness standards of maintenance facilities
- 2.8 Maintenance instructions and relationship to aircraft/aircraft component manufacturers' instructions including updating and availability to staff
- 2.9 Repair procedure
- 2.10 Aircraft maintenance programme compliance
- 2.11 Airworthiness directives procedure
- 2.12 Optional modification procedure
- 2.13 Maintenance documentation in use and its completion
- 2.14 Technical record control
- 2.15 Rectification of defects arising during base maintenance

-
- 2.16 Release to service procedure
 - 2.17 Records for the operator
 - 2.18 Reporting of defects to the CAAB/operator/manufacturer
 - 2.19 Return of defective aircraft components to store
 - 2.20 Defective components to outside contractors
 - 2.21 Control of computer maintenance record systems
 - 2.22 Control of manhour planning versus scheduled maintenance work
 - 2.23 Critical maintenance tasks and error capturing methods
 - 2.24 Reference to specific maintenance procedures such as -
 - Engine running procedures
 - Aircraft pressure run procedures
 - Aircraft towing procedures
 - Aircraft taxiing procedures
 - 2.25 Procedures to detect and rectify maintenance errors.
 - 2.26 Shift/task handover procedures
 - 2.27 Procedures for notification of maintenance data inaccuracies and ambiguities, to the type certificate holder
 - 2.28 Production planning procedures
 - 2.29 Reserved
 - 2.30 Fabrication of parts
 - 2.31 Reserved
 - 2.32 Maintenance away from approved locations

PART L2 ADDITIONAL LINE MAINTENANCE PROCEDURES

- L2.1 Line maintenance control of aircraft components, tools, equipment, etc.
- L2.2 Line maintenance procedures related to servicing/fuelling/de-icing, including inspection for/removal of de-icing/anti-icing fluid residues, etc.

- L2.3 Line maintenance control of defects and repetitive defects
- L2.4 Line procedure for completion of technical log
- L2.5 Line procedure for pooled parts and loan parts
- L2.6 Line procedure for return of defective parts removed from aircraft
- L2.7 Line procedure for Critical maintenance tasks and error capturing methods.

PART 3 QUALITY SYSTEM PROCEDURES

- 3.1 Quality audit of organisation procedures
- 3.2 Quality audit of aircraft
- 3.3 Quality audit remedial action procedure
- 3.4 Certifying staff and support staff qualification and training procedures
- 3.5 Certifying staff and support staff records
- 3.6 Quality audit personnel
- 3.7 Qualifying inspectors
- 3.8 Qualifying mechanics
- 3.9 Aircraft or aircraft component maintenance tasks exemption process control
- 3.10 Concession control for deviation from organisations' procedures
- 3.11 Qualification procedure for specialised activities such as NDT welding, etc.
- 3.12 Control of manufacturers' and other maintenance working teams
- 3.13 Human factors training procedure
- 3.14 Competence assessment of personnel
- 3.15 Training procedures for on-the-job training as per Section 6 of Appendix III to Part-66 (limited to the case where the competent authority for the Part-145 approval and for the Part-66 licence is the same).

PART 4

- 4.1 Contracting operators
- 4.2 Operator procedures and paperwork
- 4.3 Operator record completion

PART 5

- 5.1 Sample of documents
- 5.2 List of Subcontractors as per 145.A.75 (b)
- 5.3 List of Line maintenance locations as per 145.A.75 (d)
- 5.4 List of contracted organisations as per 145.A.70(a)(16)

PART 6 OPERATORS MAINTENANCE PROCEDURES

This section is reserved for those maintenance organisations approved under Part-145 who are also operators.

PART 7 (Reserved)

PART 8 (Reserved)

AMC 145.A.70(d) Maintenance organisation exposition

The Maintenance organization exposition should include a reference to the Safety Management Manual. As the CAAB issue specific approvals for each Safety Management System, the Safety Management Manual should be issued as a specific manual and not be integrated within the Maintenance organization exposition.

145.A.75 Privileges of the Organisation

In accordance with the exposition, the organisation shall be entitled to carry out the following tasks:

- (a) Maintain any aircraft and/or component for which it is approved at the locations identified in the approval certificate and in the exposition;
- (b) Arrange for maintenance of any aircraft or component for which it is approved at another organisation that is working under the quality system of the organisation. This refers to work being carried out by an organisation not itself appropriately approved to carry out such maintenance under this

Part and is limited to the work scope permitted under 145.A.65 (b) procedures. This work scope shall not include a base maintenance check of an aircraft or a complete workshop maintenance check or overhaul of an engine or engine module;

- (c) Maintain any aircraft or any component for which it is approved at any location subject to the need for such maintenance arising either from the unserviceability of the aircraft or from the necessity of supporting occasional line maintenance, subject to the conditions specified in the exposition;
- (d) Maintain any aircraft and/or component for which it is approved at a location identified as a line maintenance location capable of supporting minor maintenance and only if the organisation exposition both permits such activity and lists such locations;
- (e) Issue certificates of release to service in respect of completion of maintenance in accordance with 145.A.50.

AMC 145.A.75(b) Privileges of the organisation

1. Working under the quality system of an organisation appropriately approved under Part-145 (sub contracting) refers to the case of one organisation, not itself appropriately approved to Part-145 that carries out aircraft line maintenance or minor engine maintenance or maintenance of other aircraft components or a specialised service as a subcontractor for an organisation appropriately approved under Part-145. To be appropriately approved to subcontract the organisation should have a procedure for the control of such subcontractors as described below. Any approved maintenance organisation that carries out maintenance for another approved maintenance organisation within its own approval scope is not considered to be subcontracting for the purpose of this paragraph.
2. Maintenance of engines or engine modules other than a complete workshop maintenance check or overhaul is intended to mean any maintenance that can be carried out without disassembly of the core engine or, in the case of modular engines, without disassembly of any core module.

3. FUNDAMENTALS OF SUB-CONTRACTING UNDER PART-145

3.1 The fundamental reasons for allowing an organisation approved under Part-145 to sub-contract certain maintenance tasks are:

- (a) To permit the acceptance of specialised maintenance services, such as, but not limited to, plating, heat treatment, plasma spray, fabrication of specified parts for minor repairs / modifications, etc., without the need for direct approval by the CAAB in such cases.
- (b) To permit the acceptance of aircraft maintenance up to but not including a base maintenance check as specified in 145.A.75(b) by organisations not appropriately approved under Part-145 when it is unrealistic to expect direct approval by the CAAB. The CAAB will determine when it is unrealistic but in general it is considered unrealistic if only one or two organisations intend to use the sub-contract organisation.
- (c) To permit the acceptance of component maintenance.
- (d) To permit the acceptance of engine maintenance up to but not including a workshop maintenance check or overhaul of an engine or engine module as specified in 145.A.75(b) by organisations not appropriately approved under Part-145 when it is unrealistic to expect direct approval by the CAAB. The determination of unrealistic is as per sub-paragraph (b).

3.2 When maintenance is carried out under the sub-contract control system it means that for the duration of such maintenance, the Part-145 approval has been temporarily extended to include the sub-contractor. It therefore follows that those parts of the sub-contractor's facilities personnel and procedures involved with the maintenance organisation's products undergoing maintenance should meet Part-145 requirements for the duration of that maintenance and it remains the organisation's responsibility to ensure such requirements are satisfied.

3.3 For the criteria specified in sub-paragraph 3.1 the organisation is not required to have complete facilities for maintenance that it needs to sub-contract but it should have its own expertise to determine that the sub-contractor meets the necessary standards. However an organisation cannot be approved unless it has the in-house facilities, procedures and expertise to carry out the majority of maintenance for which it wishes to be approved in terms of the number of class ratings.

- 3.4 The organisation may find it necessary to include several specialist sub-contractors to enable it to be approved to completely certify the release to service of a particular product. Examples could be specialist welding, electro-plating, painting etc. To authorise the use of such subcontractors, the CAAB will need to be satisfied that the organisation has the necessary expertise and procedures to control such sub-contractors.
 - 3.5 An organisation working outside the scope of its approval schedule is deemed to be not approved. Such an organisation may in this circumstance operate only under the sub-contract control of another organisation approved under Part-145.
 - 3.6 Authorisation to sub-contract is indicated by the CAAB accepting the maintenance organisation exposition containing a specific procedure on the control of sub-contractors.
4. PRINCIPLE PART-145 PROCEDURES FOR THE CONTROL OF SUB-CONTRACTORS NOT APPROVED UNDER PART-145
- 4.1 A pre-audit procedure should be established whereby the maintenance organisations' subcontract control section, which may also be the 145.A.65(c) quality system independent audit section, should audit a prospective subcontractor to determine whether those services of the subcontractor that it wishes to use meets the intent of Part-145.
 - 4.2 The organisation approved under Part-145 needs to assess to what extent it will use the sub-contractor's facilities. As a general rule the organisation should require its own paperwork, approved data and material/spare parts to be used, but it could permit the use of tools, equipment and personnel from the sub-contractor as long as such tools, equipment and personnel meet the requirement of Part-145. In the case of sub-contractors who provide specialised services it may for practical reasons be necessary to use their specialised services personnel, approved data and material subject to acceptance by the organisation approved under Part-145.
 - 4.3 Unless the sub-contracted maintenance work can be fully inspected on receipt by the organisation approved under Part-145 it will be necessary for such organisation to supervise the inspection and release from the sub-contractor. Such activities should be fully described in the organisation procedure. The organisation will need to consider whether to use its own staff or authorise the sub-contractor's staff.

- 4.4 The certificate of release to service may be issued either at the sub-contractor or at the organisation facility by staff issued a certification authorisation in accordance with Part 145.A.30 as appropriate, by the organisation approved under Part-145. Such staff would normally come from the organisation approved under Part-145 but may otherwise be a person from the sub-contractor who meets the approved maintenance organisation certifying staff standard which itself is approved by the CAAB via the maintenance organisation exposition. The certificate of release to service and the CAAB Form 1 will always be issued under the maintenance organisation approval reference.
- 4.5 The sub-contract control procedure will need to record audits of the sub-contractor, to have a corrective action follow up plan and to know when sub-contractors are being used. The procedure should include a clear revocation process for sub-contractors who do not meet the Part-145 approved maintenance organisation's requirements.
- 4.6 The Part-145 quality audit staff will need to audit the sub-contract control section and sample audit sub-contractors unless this task is already carried out by the quality audit staff as stated in sub-paragraph 4.1.
- 4.7 The contract between the Part-145 approved maintenance organisation and the sub-contractor should contain a provision for the CAAB to have right of access to the sub-contractor.

145.A.85 Changes to the Organisation

The organisation shall notify the CAAB of any proposal to carry out any of the following changes before such changes take place to enable the CAAB to determine continued compliance with this Part and to amend, if necessary, the approval certificate, except that in the case of proposed changes in personnel not known to the management beforehand, these changes must be notified at the earliest opportunity:

1. the name of the organisation;
2. the main location of the organisation;
3. additional locations of the organisation;
4. the accountable manager;

5. any of the persons nominated under 145.A.30(b);
6. the facilities, equipment, tools, material, procedures, work scope or certifying staff that could affect the approval.

AMC1 145.A.85 Changes to the organisation

APPLICATION TIME FRAMES

- (a) The application for a change to an organisation certificate should be submitted at least 30 working days before the date of the intended changes.
- (b) In the case of a planned change of a nominated person, the organisation should inform the CAAB at least 20 working days before the date of the proposed change.
- (c) Unforeseen changes should be notified at the earliest opportunity, in order to enable the CAAB to determine whether there is continued compliance with the applicable requirements, and to amend, if necessary, the organisation certificate and the related terms of approval.

AMC2 145.A.85 Changes to the organisation

MANAGEMENT OF CHANGES

The organisation should manage changes to the organization. For changes requiring prior approval, it should conduct a risk assessment and provide it to the CAAB upon request.

145.A.90 Continued Validity

- (a) An approval (CAAB Form 3) shall be issued or renewed for a maximum period of two years upon the applicant demonstrating compliance with this part. It shall remain valid subject to:
 1. the organisation remaining in compliance with Part-145; and
 2. the CAAB being granted access to the organisation to determine continued compliance with this Part; and
 3. the certificate not being surrendered or revoked.
- (b) Upon surrender or revocation, the approval shall be returned to the CAAB.

145.A.95 Findings

- (a) A level 1 finding is any significant non-compliance with Part-145 requirements which lowers the safety standard and hazards seriously the flight safety.
- (b) A level 2 finding is any non-compliance with the Part-145 requirements which could lower the safety standard and possibly hazard the flight safety.
- (c) After receipt of notification of findings, the holder of the maintenance organisation approval shall define a corrective action plan and demonstrate corrective action to the satisfaction of the CAAB within a period agreed with this CAAB.

APPENDICES TO THE REGULATION**Appendix 1: Authorised Released Certificate - CAAB Form 1**

These instructions relate only to the use of the Form 1 for maintenance purposes. Attention is drawn to Part 21 which covers the use of the CAAB Form 1 for production purposes.

1. PURPOSE AND USE

- 1.1 The primary purpose of the Certificate is to declare the airworthiness of maintenance work undertaken on products, parts and appliances (hereafter referred to as 'item(s)').
- 1.2 Correlation must be established between the Certificate and the item(s). The originator must retain a Certificate in a form that allows verification of the original data.
- 1.3 The Certificate is acceptable to many airworthiness authorities, but may be dependent on the existence of bilateral agreements and/or the policy of the airworthiness authority. The 'approved design data' mentioned in this Certificate then means approved by the airworthiness authority of the importing country.
- 1.4 The Certificate is not a delivery or shipping note.
- 1.5 Aircraft are not to be released using the Certificate.
- 1.6 The Certificate does not constitute approval to install the item on a particular aircraft, engine, or propeller but helps the end user determine its airworthiness approval status.
- 1.7 A mixture of production released and maintenance released items is not permitted on the same Certificate.

2. GENERAL FORMAT

- 2.1 The Certificate must comply with the format attached including block numbers and the location of each block. The size of each block may however be varied to suit the individual application, but not to the extent that would make the Certificate unrecognisable.
- 2.2 The Certificate must be in 'landscape' format but the overall size may be significantly increased or decreased so long as the Certificate remains recognisable and legible. If in doubt consult the CAAB

-
- 2.3 The User/Installer responsibility statement can be placed on either side of the form.
 - 2.4 All printing must be clear and legible to permit easy reading.
 - 2.5 The Certificate may either be pre-printed or computer generated but in either case the printing of lines and characters must be clear and legible and in accordance with the defined format.
 - 2.6 The Certificate should be in English, and if appropriate, in one or more other languages.
 - 2.7 The details to be entered on the Certificate may be either machine/computer printed or hand-written using block letters and must permit easy reading.
 - 2.8 Limit the use of abbreviations to a minimum, to aid clarity.
 - 2.9 The space remaining on the reverse side of the Certificate may be used by the originator for any additional information but must not include any certification statement. Any use of the reverse side of the Certificate must be referenced in the appropriate block on the front side of the Certificate.
3. COPIES
 - 3.1 There is no restriction in the number of copies of the Certificate sent to the customer or retained by the originator.
4. ERROR(S) ON A CERTIFICATE
 - 4.1 If an end-user finds an error(s) on a Certificate, he must identify it/them in writing to the originator. The originator may issue a new Certificate only if the error(s) can be verified and corrected.
 - 4.2 The new Certificate must have a new tracking number, signature and date.
 - 4.3 The request for a new Certificate may be honoured without re-verification of the item(s) condition. The new Certificate is not a statement of current condition and should refer to the previous Certificate in block 12 by the following statement; “This Certificate corrects the error(s) in block(s) [enter block(s) corrected] of the Certificate [enter original tracking number] dated [enter original issuance date] and does not cover conformity/condition/release to service”. Both Certificates should be retained according to the retention period associated with the first.

5. COMPLETION OF THE CERTIFICATE BY THE ORIGINATOR

Block 1 CAA Bangladesh

State the name of the CAAB

Block 2 CAAB Form 1 header:

Block 3 Form Tracking Number

Enter the unique number established by the numbering system/procedure of the organisation identified in block 4; this may include alpha/numeric characters.

Block 4 Organisation Name and Address

Enter the full name and address of the approved organisation (refer to Form 3) releasing the work covered by this Certificate. Logos, etc., are permitted if the logo can be contained within the block.

Block 5 Work Order/Contract/Invoice

To facilitate customer traceability of the item(s), enter the work order number, contract number, invoice number, or similar reference number.

Block 6 Item

Enter line item numbers when there is more than one line item. This block permits easy cross-referencing to the Remarks block 12.

Block 7 Description

Enter the name or description of the item. Preference should be given to the term used in the instructions for continued airworthiness or maintenance data (e.g. Illustrated Parts Catalogue, Aircraft Maintenance Manual, Service Bulletin, Component Maintenance Manual).

Block 8 Part Number

Enter the part number as it appears on the item or tag/packaging. In case of an engine or propeller the type designation may be used.

Block 9 Quantity

State the quantity of items.

Block 10 Serial Number

If the item is required by regulations to be identified with a serial number, enter it here. Additionally, any other serial number not required by regulation may also be entered. If there is no serial number identified on the item, enter "N/A".

Block 11 Status/Work

The following describes the permissible entries for block 11. Enter only one of these terms – where more than one may be applicable, use the one that most accurately describes the majority of the work performed and/or the status of the article.

(i) Overhauled: Means a process that ensures the item is in complete conformity with all the applicable service tolerances specified in the type certificate holder's, or equipment manufacturer's instructions for continued airworthiness, or in the data which is approved or accepted by the Authority. The item will be at least disassembled, cleaned, inspected, repaired as necessary, reassembled and tested in accordance with the above specified data.

(ii) Repaired: Rectification of defect(s) using an applicable standard.*

(iii) Inspected/Tested: Examination, measurement, etc. in accordance with an applicable standard* (e.g. visual inspection, functional testing, bench testing etc.).

(iv) Modified: Alteration of an item to conform to an applicable standard.

*Applicable standard means a manufacturing / design / maintenance / quality standard, method, technique or practice approved by or acceptable to the CAAB. The applicable standard shall be described in block 12.

Block 12 Remarks

Describe the work identified in Block 11, either directly or by reference to supporting documentation, necessary for the user or installer to determine the airworthiness of item(s) in relation to the work being certified. If necessary, a separate sheet may be used and referenced from the main Form 1. Each statement must clearly identify which item(s) in Block 6 it relates to.

Examples of information to be entered in block 12 are:

- (i) Maintenance data used, including the revision status and reference.
- (ii) Compliance with airworthiness directives or service bulletins.

- (iii) Repairs carried out.
- (iv) Modifications carried out.
- (v) Replacement parts installed.
- (vi) Life limited parts status.
- (vii) Deviations from the customer work order.
- (viii) Release statements to satisfy a foreign Civil Aviation Authority maintenance requirement.
- (ix) Information needed to support shipment with shortages or re-assembly after delivery.
- (x) For maintenance organisations approved in accordance with Subpart F of Part-M, the component certificate of release to service statement referred to in point M.A.613:

“Certifies that, unless otherwise specified in this block, the work identified in block 11 and described in this block was accomplished in accordance to the requirements of Section A, Subpart F of Part-M and in respect to that work the item is considered ready for release to service. THIS IS NOT A RELEASE UNDER PART-145.”

If printing the data from an electronic Form 1, any appropriate data not fit for other blocks should be entered in this block.

Block 13a-13e

General Requirements for blocks 13a-13e: Not used for maintenance release. Shade, darken, or otherwise mark to preclude inadvertent or unauthorised use.

Block 14a

Mark the appropriate box(es) indicating which regulations apply to the completed work. If the box “other regulations specified in block 12” is marked, then the regulations of the other airworthiness authority(ies) must be identified in block 12. At least one box must be marked, or both boxes may be marked, as appropriate.

For all maintenance carried out by maintenance organisations approved in accordance with Section A, Subpart F Part M, the box “other regulation specified in block 12” shall be ticked and the certificate of release to service statement made in block 12. In that case, the certification statement “unless otherwise specified in this block” is intended to address the following cases;

- (a) Where the maintenance could not be completed.
- (b) Where the maintenance deviated from the standard required by Part-M.
- (c) Where the maintenance was carried out in accordance with a requirement other than that specified in Part-M. In this case block 12 shall specify the particular national regulation.

For all maintenance carried out by maintenance organisations approved in accordance with Section A of Part-145, the certification statement “unless otherwise specified in block 12” is intended to address the following cases;

- (a) Where the maintenance could not be completed.
- (b) Where the maintenance deviated from the standard required by Annex II (Part-145).
- (c) Where the maintenance was carried out in accordance with a requirement other than that specified in Part-145. In this case block 12 shall specify the particular national regulation.

Block 14b Authorised Signature

This space shall be completed with the signature of the authorised person. Only persons specifically authorised under the rules and policies of the CAAB are permitted to sign this block. To aid recognition, a unique number identifying the authorised person may be added.

Block 14c Certificate/Approval Number

Enter the Certificate/Approval number/reference. This number or reference is issued by the CAAB.

Block 14d Name

Enter the name of the person signing block 14b in a legible form.

Block 14e Date

Enter the date on which block 14b is signed, the date must be in the format dd = 2 digit day, mmm = first 3 letters of the month, yyyy = 4 digit year

User/Installer Responsibilities

Place the following statement on the Certificate to notify end users that they are not relieved of their responsibilities concerning installation and use of any item accompanied by the form:

“THIS CERTIFICATE DOES NOT AUTOMATICALLY CONSTITUTE AUTHORITY TO INSTALL.

WHERE THE USER/INSTALLER PERFORMS WORK IN ACCORDANCE WITH REGULATIONS OF AN AIRWORTHINESS AUTHORITY DIFFERENT THAN THE AIRWORTHINESS AUTHORITY SPECIFIED IN BLOCK 1, IT IS ESSENTIAL THAT THE USER/INSTALLER ENSURES THAT HIS/HER AIRWORTHINESS AUTHORITY ACCEPTS ITEMS FROM THE AIRWORTHINESS AUTHORITY SPECIFIED IN BLOCK 1.

STATEMENTS IN BLOCKS 13A AND 14A DO NOT CONSTITUTE INSTALLATION CERTIFICATION. IN ALL CASES AIRCRAFT MAINTENANCE RECORDS MUST CONTAIN AN INSTALLATION CERTIFICATION ISSUED IN ACCORDANCE WITH THE NATIONAL REGULATIONS BY THE USER/INSTALLER BEFORE THE AIRCRAFT MAY BE FLOWN.”

**“AUTHORISED RELEASE CERTIFICATE
CAAB FORM 1”**

1. Civil Aviation Authority of Bangladesh		2. AUTHORISED RELEASE CERTIFICATE CAAB FORM 1			3. Form Tracking Number	
4. Organisation Name and Address:						
6. Item	7. Description	8. Part No.	9. Qty.	10. Serial No.	11. Status/Work	
12. Remarks						
13a. Certifies that the items identified above were manufactured in conformity to: <input type="checkbox"/> approved design data and are in a condition for safe operation <input type="checkbox"/> non-approved design data specified in block 12		14a. <input type="checkbox"/> Part-145.A.50 Release to Service <input type="checkbox"/> Other regulation specified in block 12 12. Certifies that unless otherwise specified in block 12, the work identified in block 11 and described in block 12, was accomplished in accordance with Part-145 and in respect to that work the items are considered ready for release to service.				
13b. Authorised Signature		13c. Approval/ Authorisation Number		14b. Authorised Signature		14c. Certificate/Approval Ref. No.
13d. Name		13c. Date (dd mmm yyyy)		14d. Name		14e. Date (dd mmm yyyy)
USER/INSTALLER RESPONSIBILITIES						
This certificate does not automatically constitute authority to install the item(s). Where the user/installer performs work in accordance with regulations of an airworthiness authority different than the airworthiness authority specified in block 1, it is essential that the user/installer ensures that his/her airworthiness authority accepts items from the airworthiness authority specified in block 1. Statements in blocks 13a and 14a do not constitute installation certification. In all cases aircraft maintenance records must contain an installation certification issued in accordance with the national regulations by the user/installer before the aircraft may be flown.						

Appendix II - Class and Ratings System used for the Approval of Maintenance Organizations referred to Part-145

1. Except as stated otherwise for the smallest organisations in paragraph 12, the table referred to in point 13 provides the standard system for the approval of maintenance organisation under Subpart F Part-M and Part-145. An organisation must be granted an approval ranging from a single class and rating with limitations to all classes and ratings with limitations.
2. In addition to the table referred to in point 13, the approved maintenance organisation is required to indicate its scope of work in its maintenance organisation manual/exposition. See also paragraph 11.
3. Within the approval class(es) and rating(s) granted by the CAAB the scope of work specified in the maintenance organisation exposition defines the exact limits of approval. It is therefore essential that the approval class(es) and rating(s) and the organisations scope of work are matching.
4. A category A class rating means that the approved maintenance organisation may carry out maintenance on the aircraft and any component (including engines and/or Auxiliary Power Units (APUs), in accordance with aircraft maintenance data or, if agreed by the CAAB, in accordance with component maintenance data, only whilst such components are fitted to the aircraft. Nevertheless, such A-rated approved maintenance organisation may temporarily remove a component for maintenance, in order to improve access to that component, except when such removal generates the need for additional maintenance not eligible for the provisions of this paragraph. This will be subject to a control procedure in the maintenance organisation exposition to be approved by the CAAB. The limitation section will specify the scope of such maintenance thereby indicating the extent of approval.
5. A category B class rating means that the approved maintenance organisation may carry out maintenance on the uninstalled engine and/or APU and engine and/or APU components, in accordance with engine and/or APU maintenance data or, if agreed by the CAAB, in accordance with component maintenance data, only whilst such components are fitted to the engine and/or APU. Nevertheless, such B-rated approved maintenance organisation may temporarily remove a component for maintenance, in order to improve access to that component, except when such removal generates the need for additional maintenance not eligible for the provisions of this paragraph. The limitation section will specify the scope of such maintenance thereby indicating the extent of approval. A maintenance organisation approved with a category B class rating may also carry out maintenance on an installed engine during 'base' and 'line' maintenance subject to a control procedure in the maintenance organisation exposition to be approved by the CAAB. The maintenance organisation exposition scope of work shall reflect such activity where permitted by the CAAB.

6. A category C Class rating means that the approved maintenance organisation may carry out maintenance on uninstalled components (excluding engines and APUs) intended for fitment to the aircraft or engine/APU. The limitation section will specify the scope of such maintenance thereby indicating the extent of approval. A maintenance organisation approved with a category C class rating may also carry out maintenance on an installed component during base and line maintenance or at an engine/APU maintenance facility subject to a control procedure in the maintenance organisation exposition to be approved by the CAAB. The maintenance organisation exposition scope of work shall reflect such activity where permitted by the CAAB.
7. A category D class rating is a self-contained class rating not necessarily related to a specific aircraft, engine or other component. The D1 - Non Destructive Testing (NDT) rating is only necessary for an approved maintenance organisation that carries out NDT as a particular task for another organisation. A maintenance organisation approved with a class rating in A or B or C category may carry out NDT on products it is maintaining subject to the maintenance organisation exposition containing NDT procedures, without the need for a D1 class rating.
8. In the case of maintenance organisations approved in accordance with Part-145, category A class ratings are subdivided into 'Base' or 'Line' maintenance. Such an organisation may be approved for either 'Base' or 'Line' maintenance or both. It should be noted that a 'Line' facility located at a main base facility requires a 'Line' maintenance approval.
9. The 'limitation' section is intended to give CAAB maximum flexibility to customise the approval to a particular organisation. Table 1 specifies the types of limitation possible and whilst maintenance is listed last in each class rating it is acceptable to stress the maintenance task rather than the aircraft or engine type or manufacturer, if this is more appropriate to the organisation. An example could be avionics systems installations and maintenance.
10. When reference is made to series, type and group in the limitation section of class A and B, series means a specific type series such as Airbus 300 or 310 or 319 or Boeing 737-300 series or RB211-524 series or Cessna 150 or Cessna 172 or Beech 55 series or continental O-200 series etc; type means a specific type or model such as Airbus 310-240 type or RB 211-524 B4 type or Cessna 172RG type; any number of series or types may be quoted; group means for example Cessna single piston engine aircraft or Lycoming non-supercharged piston engines etc.

11. When a lengthy capability list is used which could be subject to frequent amendment, then such amendment shall be in accordance with a procedure acceptable to CAAB and included in the maintenance organisation exposition. The procedure shall address the issues of who is responsible for capability list amendment control and the actions that need to be taken for amendment. Such actions include ensuring compliance with Part-145 for products or services added to the list.
12. A maintenance organisation which employs only one person to both plan and carry out all maintenance can only hold a limited scope of approval rating. The maximum permissible limits are:

CLASS	RATING	LIMITATION
CLASS AIRCRAFT	RATING A2 AEROPLANES 5700 KG AND BELOW	PISTON ENGINE 5700 KG AND BELOW
CLASS AIRCRAFT	RATING A3 HELICOPTERS	SINGLE PISTON ENGINE 3175 KG AND BELOW
CLASS AIRCRAFT	RATING A4 AIRCRAFT OTHER THAN A1, A2 AND A3	NO LIMITATION
CLASS ENGINES	RATING B2 PISTON	LESS THAN 450 HP
CLASS COMPONENTS RATING OTHER THAN COMPLETE ENGINES OR APU'S.	C1 TO C22	AS PER CAPABILITY LIST
CLASS SPECIALISED	D1 NDT	NDT METHOD(S) TO BE SPECIFIED.

It should be noted that such an organisation may be further limited by the CAAB in the scope of approval dependent upon the capability of the particular organisation.

13. Table

CLASS	RATING	LIMITATION	BASE	LINE
AIRCRAFT	A1 Aeroplanes above 5700 kg	[Rating reserved to Maintenance Organisations approved in accordance with Annex II (Part-145)] [Shall state aeroplane manufacturer or group or series or type and/or the maintenance tasks] Example: Airbus A320 Series	[YES/NO]*	[YES/NO]*
	A2 Aeroplanes 5700 kg and below	[Shall state aeroplane manufacturer or group or series or type and/or the maintenance tasks] Example: DHC-6 Twin Otter Series	[YES/NO]*	[YES/NO]*
	A3 Helicopters	[Shall state helicopter manufacturer or group or series or type and/or the maintenance task(s)] Example: Robinson R44	[YES/NO]*	[YES/NO]*
	A4 Aircraft other than A1, A2 and A3	[Shall state aircraft series or type and/or the maintenance task(s).]	[YES/NO]*	[YES/NO]*
ENGINES	B1 Turbine	[Shall state engine series or type and/or the maintenance task(s)] Example: PT6A Series		
	B2 Piston	[Shall state engine manufacturer or group or series or type and/or the maintenance task(s)]		
	B3 APU	[Shall state engine manufacturer or series or type and/or the maintenance task(s)]		
COMPONENTS OTHER THAN COMPLETE ENGINES OR APUs	C1 Air Cond & Press			
	C2 Auto Flight			
	C3 Comms and Nav			
	C4 Doors - Hatches			
	C5 Electrical Power & Lights			
	C6 Equipment			
	C7 Engine - APU			
	C8 Flight Controls			
	C9 Fuel			
	C10 Helicopter - Rotors			
	C11 Helicopter - Trans			
	C12 Hydraulic Power			
	C13 Indicating - recording system			
	C14 Landing Gear			
	C15 Oxygen			
	C16 Propellers			
	C17 Pneumatic & Vacuum			
	C18 Protection ice/rain/fire			
	C19 Windows			
	C20 Structural			
	C21 Water ballast Structural			
	C22 Propulsion Augmentation			
SPECIALISED SERVICES	D1 Non Destructive Testing	[Shall state particular NDT method(s)]		

Appendix III - Maintenance Organisation Approval referred to in Part-145(CAAB Form 3)**CIVIL AVIATION AUTHORITY OF BANGLADESH****MAINTENANCE ORGANISATION APPROVAL CERTIFICATE**

Reference: CAAB.145.YYY

Pursuant to Civil Aviation Authority of Bangladesh regulations and Part -145 for the time being in force and subject to the conditions specified below, the CAAB hereby certifies:

[COMPANY NAME]

[COMPANY ADDRESS]

as a maintenance organisation in compliance with Section A of Part-145, approved to maintain products, parts and appliances listed in the attached approval schedule and issue related certificates of release to service using the above references.

CONDITIONS:

1. This approval is limited to that specified in the scope of work section of the Part 145 approved maintenance organisation exposition as referred to in Section A of Part-145, and
2. This approval requires compliance with the procedures specified in the Part 145 approved maintenance organisation exposition, and
3. This approval is valid whilst the approved maintenance organisation remains in compliance with Part-145.
4. Subject to compliance with the foregoing conditions, this approval shall remain valid for a duration of Two (02) years unless the approval has previously been surrendered, superseded, suspended or revoked.

Date of original issue :

Date of this revision :

Revision No :

Signed :

Name & Designation
Airworthiness & Engineering Division
For the Chairman,
Civil Aviation Authority of Bangladesh

MAINTENANCE ORGANISATION APPROVAL SCHEDULE

Reference: CAAB.145.YYY

Organisation: [COMPANY NAME AND ADDRESS]

CLASS	RATING	LIMITATION	BASE	LINE
AIRCRAFT (**)	(***)	(***)	[YES/NO](**)	[YES/NO](**)
	(***)	(***)	[YES/NO](**)	[YES/NO](**)
	(***)	(***)	[YES/NO](**)	[YES/NO](**)
	(***)	(***)	[YES/NO](**)	[YES/NO](**)
ENGINES (**)	(***)	(***)		
	(***)	(***)		
COMPONENTS OTHER THAN COMPLETE ENGINES OR APUs (**)	(***)	(***)		
	(***)	(***)		
	(***)	(***)		
	(***)	(***)		
	(***)	(***)		
	(***)	(***)		
SPECIALISED SERVICES (**)	(***)	(***)		
	(***)	(***)		

This approval schedule is limited to those products, parts and appliances and to the activities specified in the scope of work section of the Part-145 approved maintenance organisation exposition,

Maintenance Organisation Exposition reference:

Date of original issue:

Date of last revision approved: Revision No:

Signed :

Name & Designation
Airworthiness & Engineering Division
For the Chairman,
Civil Aviation Authority of Bangladesh

AMC to Appendix III Maintenance Organisation Approval referred to in Part-145

The following fields on page 2 “Maintenance Organisation Approval Schedule” of the maintenance organisation approval certificate should be completed as follows:

Date of original issue:

It refers to the date of the original issue of the maintenance organisation exposition.

Date of last revision approved:

It refers to the date of the last revision of the maintenance organisation exposition affecting the content of the certificate. Changes to the maintenance organisation exposition which do not affect the content of the certificate do not require the reissuance of the certificate.

Revision No:

It refers to the revision No of the last revision of the maintenance organisation exposition affecting the content of the certificate. Changes to the maintenance organisation exposition which do not affect the content of the certificate do not require the reissuance of the certificate.

Appendix IV - Conditions for the use of staff not qualified in accordance with Part-66 referred to in points 145.A.30(j)1 and 2.

1. Certifying staff in compliance with the following conditions are deemed to meet the intent of point 145.A.30(j)(1) and (2):
 - (a) The person shall hold a licence or a certifying staff authorisation issued under the national regulations in full compliance with ICAO Annex 1.
 - (b) The scope of work of the person shall not exceed the scope of work defined by the national licence or the certifying staff authorisation, whatever is the most restrictive.
 - (c) The person shall demonstrate he/she received the training on human factors and aviation legislation referred to in modules 9 and 10 of Appendix I to Part-66.
 - (d) The person shall demonstrate five years maintenance experience for line maintenance certifying staff and eight years for base maintenance certifying staff. However, those persons whose authorised tasks do not exceed those of a Part-66 category A certifying staff, need to demonstrate three years maintenance experience only.
 - (e) Line maintenance certifying staff and base maintenance support staff demonstrate he/she received type training and passed examination at the category B1, B2 or B3 level, as applicable, referred to in Appendix III to Part-66 for each aircraft type in the scope of work referred to in point (b). Those persons whose scope of work does not exceed those of a category A certifying staff may however receive task training in lieu of complete type training.
 - (f) Base maintenance certifying staff shall demonstrate he/she received type training and passed examination at the category C level referred to in Appendix III to Part-66 for each aircraft type in the scope of work referred to in point (b), except that for the first aircraft type, training and examination shall be at the category B1, B2 or B3 level of Appendix III.
2. Protected rights
 - (a) The personnel having privileges before the entry into force of the ANO Part-66 may continue to exercise them without the need to comply with points 1(c) to 1(f).
 - (b) However after that date any certifying staff willing to extend the scope of their authorisation to include additional privileges shall comply with point 1.
 - (c) Notwithstanding subparagraph 2(b) above, in the case of additional type training, compliance with points 1(c) and 1(d) is not required.

Appendix V – Safety Management System (SMS)

1. Scope

This appendix establishes the minimum requirements Safety Management System of maintenance organization complying with Part 145 should meet. The maintenance organization may wish to follow more stringent requirements.

2. Definitions

Acceptable level of safety means minimum safety performance that a maintenance organisation should achieve while conducting their core business functions, expressed by a number of safety performance indicators and safety performance targets.

Accountability means obligation or willingness to account for one's actions.

Accountable Executive means a single, identifiable person which might be a Chief Executive Officer, a Chairperson Board of Directors, a partner or a proprietor who has full responsibility for the organization's SMS and have full authority for human resources issues, major financial issues, direct responsibility for the conduct of the organization's affairs, final authority over operations under certificate, and final responsibility for all safety issues.

Consequence means potential outcome(s) of the hazard.

Hazard means condition, object or activity with the potential of causing injuries to personnel, damage to equipment or structures, loss of material, or reduction of ability to perform a prescribed function.

Mitigation means measures to address the potential hazard or to reduce the risk probability or severity.

Predictive means a method that captures system performance as it happens in real-time normal operations.

Proactive means the adoption of an approach which emphasizes prevention through the identification of hazards and the introduction of risk mitigation measures before the risk-bearing event occurs and adversely affects safety performance.

Probability means the likelihood that an unsafe event or condition might occur.

Reactive means the adoption of an approach where safety measurement is as a responds to the events that already happened, such as incidents and accidents.

Risk means the assessment, expressed in terms of predicted probability and severity, of the consequence(s) of a hazard taking as reference the worst foreseeable situation.

Risk management means the identification, analysis and elimination, and/or mitigation to an acceptable level of risks that threaten the capabilities of an organization.

Safety means the state in which the risk of harm to persons or property damage is reduced to, and maintained at or below, an acceptable level through a continuing process of hazard identification and risk management.

Safety assessment means a systematic analysis of a proposed change to equipment or procedures to identify and mitigate weaknesses before change is implemented.

Safety assurance means what the maintenance organisation do with regard to safety performance monitoring and measurement.

Safety audit means what the Civil Aviation Authority performs with regard to its safety programme, and the maintenance organisations perform with regard to the SMS.

Safety Management System (SMS) means a systematic approach to managing safety, including the necessary organizational structures, accountabilities, policies and procedures.

Safety manager means a person who is responsible for providing guidance and direction for the operation of the organization's safety management system.

Safety oversight means the activities of Civil Aviation Authority as part of its safety programme, performed with regard to the maintenance organisation SMS, in order to confirm the organization's continuing fulfillment of its corporate safety policy, objectives, goals and standards.

Safety performance indicator means established objectives of a maintenance organisation SMS, linked to major components of a services provider SMS, and expressed in numerical terms.

Safety performance monitoring means the activities of a maintenance organization as part of its SMS, in order to confirm the organization's continuing fulfillment of its corporate safety policy, objectives, goals and standards.

Safety performance target means medium or long-term objectives of a maintenance organisation SMS, determined weighing what is desirable and what is realistic for an individual services provider, and expressed in numerical terms.

Safety policy means a statement reflecting the organization's philosophy of safety management, and become the foundation on which the organization's SMS is built. The safety policy outlines the methods and processes that the organization will use to achieve desired safety outcomes.

Safety programme means an integrated set of regulations and activities aimed at improving safety.

Safety requirement means the operational procedures, technology, systems and programmes to which measures of reliability, availability, performance and/or accuracy can be specified.

Severity means the possible consequences of an unsafe event or condition, taking as reference the worst foreseeable situation.

System means organized set of processes and procedures.

Systematic means that safety management activities will be conducted in accordance with a pre-determined plan, and applied in a consistent manner throughout the organization.

3. General

The maintenance organisation shall establish, maintain and adhere to a Safety Management System (SMS) that is appropriate to the size, nature and complexity of its scope of work and the safety hazards and risks related to it.

4. Safety policy and objectives

4.1 General requirements

- (1) A maintenance organisation shall define the organization's safety policy.
- (2) The safety policy shall be signed by the Accountable Executive of the organization.
- (3) The safety policy shall be in accordance with all applicable legal requirements and international standards, best industry practices and shall reflect organizational commitments regarding safety.
- (4) The safety policy shall be communicated, with visible endorsement, throughout the organization.
- (5) The safety policy shall include a clear statement about the provision of the necessary human and financial resources for its implementation.
- (6) The safety policy shall, among other things, include the following objectives:

-
- (a) Commitment to implement an SMS;
 - (b) Commitment to continual improvement in the level of safety;
 - (c) Commitment to the management of safety risks;
 - (d) Commitment to encourage employees to report safety issues;
 - (e) Establishment of clear standards for acceptable behaviour; and
 - (f) Identification of responsibilities of management and employees with respect to safety performance.
- (7) The safety policy shall be reviewed periodically to ensure it remains relevant and appropriate to the organization.
 - (8) A maintenance organisation shall establish safety objectives for the SMS.
 - (9) The safety objectives should be linked to the safety performance indicators, safety performance targets and safety requirements of the maintenance organisation SMS.

4.2 Organizational structure and responsibilities

- (1) A maintenance organisation shall identify an Accountable Executive to be responsible and accountable on behalf of the maintenance organisation for meeting the requirements of this regulation, and shall notify the CAAB the name of the person.
- (2) The Accountable Executive shall be a single, identifiable person who, irrespective of other functions, shall have the ultimate responsibility for the implementation and maintenance of the SMS.
- (3) The Accountable Executive shall have:
 - (a) Full control of the human resources required for the work authorized to be conducted under the maintenance organization approval;
 - (b) Full control of the financial resources required for the work authorized to be conducted under the maintenance organization approval;
 - (c) Final authority over the work authorized to be conducted under the maintenance organization approval;
 - (d) Direct responsibility for the conduct of the organization's affairs; and
 - (e) Final responsibility for all safety issues.

- (4) A maintenance organisation shall establish the safety structure necessary for the implementation and maintenance of the organization's SMS.
- (5) A maintenance organisation shall identify the safety responsibilities of all members of senior management, irrespective of other responsibilities.
- (6) Safety-related positions, responsibilities and authorities shall be defined, documented and communicated throughout the organization.
- (7) A maintenance organisation shall identify a Safety Manager to be the member of management who shall be the responsible individual and focal point for the development and maintenance of an effective SMS.
- (8) The Safety Manager shall:
 - (a) Ensure that processes needed for the SMS are established, implemented and maintained;
 - (b) Report to the Accountable Executive on the performance of the SMS and on any need for improvement; and
 - (c) Ensure safety promotion throughout the organization.

4.3 SMS implementation plan

- (1) A maintenance organisation shall develop and maintain an SMS implementation plan.
- (2) The SMS implementation plan shall be the definition of the approach the organization will adopt for managing safety in a manner that will meet the organization's safety needs.
- (3) The SMS implementation plan shall include the following:
 - (a) Safety policy and objectives;
 - (b) Safety planning,
 - (c) System description;
 - (d) Gap analysis;
 - (e) SMS components;
 - (f) Safety roles and responsibilities;
 - (g) Safety reporting policy;
 - (h) Means of employee involvement;
 - (i) Safety training;

-
- (j) Safety communication;
 - (k) Safety performance measurement; and
 - (l) Management review of safety performance.
- (4) The SMS implementation plan shall be endorsed by senior management of the organization.
- (5) A maintenance organisation shall, as part of the development of the SMS implementation plan, complete a system description.
- (6) The system description shall include the following:
- (a) The system interactions with other systems in the air transportation system;
 - (b) The system functions;
 - (c) Required human performance considerations of the system operation;
 - (d) Hardware components of the system;
 - (e) Software components of the system;
 - (f) Related procedures that define guidance for the operation and use of the system;
 - (g) Operational environment; and
 - (h) Contracted and purchased products and services.
- (7) A maintenance organisation shall, as part of the development of the SMS implementation plan, complete a gap analysis, in order to:
- (a) Identify the safety arrangements and structures that may be already exist throughout an organization; and
 - (b) Determine additional safety arrangements required to implement and maintain the organization's SMS.
- (8) The SMS implementation plan shall explicitly address the coordination between the SMS of the maintenance organisation and the SMS of other organizations the maintenance organisation must interface with during the provision of services.

4.4 Coordination of emergency response planning

A maintenance organisation shall develop and maintain, or coordinate, as appropriate, an emergency response/contingency plan that shall ensure:

- (1) Orderly and efficient transition from normal to emergency situation;
- (2) Designation of emergency authority;
- (3) Assignment of emergency responsibilities;
- (4) Coordination of efforts to cope with the emergency; and
- (5) Safe continuation of its activities, or return to normal activities as soon as possible.

4.5 Documentation

- (1) A maintenance organisation shall develop and maintain SMS documentation, in paper or electronic form, to describe the following:
 - (a) Safety policy;
 - (b) Safety objectives;
 - (c) SMS requirements, procedures and processes;
 - (d) Responsibilities and authorities for procedures and processes; and
 - (e) SMS outputs.
- (2) A maintenance organisation shall, as part of the SMS documentation, develop and maintain a Safety Management System Manual (SMSM), to communicate the organization's approach to safety throughout the organization.
- (3) The SMSM shall document all aspects of the SMS, and its contents shall include the following:
 - (a) Scope of the Safety Management System;
 - (b) Safety policy and objectives;
 - (c) Safety accountabilities;
 - (d) Key safety personnel;
 - (e) Documentation control procedures;
 - (f) Hazard identification and risk management schemes;
 - (g) Safety performance monitoring;
 - (h) Emergency response/contingency planning;
 - (i) Management of change; and
 - (j) Safety promotion.

5. Safety risk management

5.1 General

- (1) A maintenance organisation shall develop and maintain Safety Data Collection and Processing systems (SDCPS) that provide for the identification of hazards and the analysis, assessment and mitigation of safety risks.
- (2) A maintenance organisation's SDCPS shall include reactive, proactive and predictive methods of safety data collection.

5.2 Hazard identification

- (1) A maintenance organisation shall develop and maintain formal means for effectively collecting, recording, acting on and generating feedback about hazards in its activities, which combine reactive, proactive and predictive methods of safety data collection. Formal means of safety data collection shall include mandatory, voluntary and confidential reporting systems.
- (2) The hazard identification process shall include the following steps:
 - (a) Reporting of hazards, events or safety concerns;
 - (b) Collection and storing the safety data;
 - (c) Analysis of the safety data; and
 - (d) Distribution of the safety information distilled from the safety data.

5.3 Risk management

- (1) A maintenance organisation shall develop and maintain a formal risk management process that ensures the analysis, assessment and mitigation of risks of consequences of hazards to an acceptable level.
- (2) The risks of the consequences of each hazard identified through the hazard identification processes described in section 7.2 of this regulation shall be analysed in terms of probability and severity of occurrence, and assessed for their tolerability.
- (3) The organization shall define the levels of management with authority to make safety risk tolerability decisions.

6. Safety assurance

6.1 General

- (1) A maintenance organisation shall develop and maintain safety assurance processes to ensure that the safety risks controls developed as a consequence of the hazard identification and risk management activities under paragraph 7 achieve their intended objectives.

- (2) Safety assurance processes shall apply to an SMS whether the activities are accomplished internally or outsourced.

6.2 Safety performance monitoring and measurement

- (1) A maintenance organisation shall, as part of the SMS safety assurance activities, develop and maintain the necessary means to verify safety performance of the organization in comparison with the approved safety policies and objectives, and to validate the effectiveness of implemented safety risk controls.
- (2) Safety performance monitoring and measurement means shall include the following:
 - (a) Safety reporting,
 - (b) Safety audits,
 - (c) Safety surveys,
 - (d) Safety reviews,
 - (e) Safety studies, and
 - (f) Internal safety investigations.
- (3) The safety reporting procedure shall set out the conditions to ensure effective safety reporting, including the conditions under protection from disciplinary/administrative action shall apply.

6.3 Management of change

- (1) A maintenance organisation shall, as part of the SMS safety assurance activities, develop and maintain a formal process for the management of change.
- (2) The formal process for the management of change shall:
 - (a) Identify changes within the organization which may affect established processes and services;
 - (b) Describe the arrangements to ensure safety performance before implementing changes; and
 - (c) Eliminate or modify safety risk controls that are no longer needed due to changes in the operational environment.

6.4 Continuous improvement of the safety system

- (1) A maintenance organisation shall, as part of the SMS safety assurance activities, develop and maintain formal processes to identify the causes of under-performance of the SMS, determine the implications in its operation, and to rectify situations involving below standard performance in order to ensure the continual improvement of the SMS.
- (2) Continuous improvement of the maintenance organisation SMS shall include:
 - (a) Proactive and reactive evaluations of facilities, equipment, documentation and procedures, to verify the effectiveness of strategies for control of safety risks; and
 - (b) Proactive evaluation of the individuals' performance, to verify the fulfilment of safety responsibilities.

7. Safety promotion**7.1 General**

A maintenance organisation shall develop and maintain formal safety training and safety communication activities to create an environment where the safety objectives of the organization can be achieved.

7.2 Safety training

- (1) A maintenance organisation shall, as part of its safety promotion activities, develop and maintain a safety training programme that ensures that personnel are trained and competent to perform the SMS duties.
- (2) The scope of the safety training shall be appropriate to the individual's involvement in the SMS.
- (3) The Accountable Executive shall receive safety awareness training regarding:
 - (a) Safety policy and objectives;
 - (b) SMS roles and responsibilities; and
 - (c) Safety assurance.

7.3 Safety communication

- (1) A maintenance organisation shall, as part of its safety promotion activities, develop and maintain formal means for safety communication, to:

-
- (a) Ensure that all staff is fully aware of the SMS;
 - (b) Convey safety critical information;
 - (c) Explain why particular safety actions are taken;
 - (d) Explain why safety procedures are introduced or changed; and
 - (e) Convey generic safety information.
- (2) Formal means of safety communication shall include:
- (a) Safety policies and procedures;
 - (b) News letters; and
 - (c) Bulletins.

7.4 Quality policy

A maintenance organisation shall ensure that the organization quality policy is consistent with, and supports the fulfillment of the activities of the SMS.

APPENDICES TO AMCs
Appendix I: CAAB Form 4

CIVIL AVIATION AUTHORITY BANGLADESH	
<p>Details of Nominated Personnel required to be accepted as specified in <i>(Please tick (✓) in the appropriate box)</i></p>	<p><input type="checkbox"/> ANO Part- 145</p> <p><input type="checkbox"/> ANO Part- M</p> <p style="text-align: center;">Subpart F</p> <p><input type="checkbox"/> ANO Part- M</p> <p style="text-align: center;">Subpart G</p>
1. Name : -----	
2. Position: -----	
3. Qualifications relevant to the item (2) Position:	
4. Work Experience relevant to the item (2) Position:	
Signature -----	Date: -----
On Completion, please send this form under confidential cover to the Chairman, CAAB	
CAAB Use Only	
Name and signature of authorised CAAB Official accepting this person:	
Signature -----	Date -----
Name -----	Office -----

CAAB Form 4

Appendix III to AMC 145.A.15: CAAB Form 2

CIVIL AVIATION AUTHORITY OF BANGLADESH**Application for*****Please tick (✓) in the appropriate the boxes:***

- | | | | |
|---|---|----------------------------------|-----------------------------------|
| <input type="checkbox"/> ANO Part- 145 Approval | <input type="checkbox"/> initial grant* | <input type="checkbox"/> Change* | <input type="checkbox"/> Renewal* |
| <input type="checkbox"/> ANO Part- M Subpart F Approval | <input type="checkbox"/> initial grant* | <input type="checkbox"/> Change* | <input type="checkbox"/> Renewal* |
| <input type="checkbox"/> ANO Part- M Subpart G Approval | <input type="checkbox"/> initial grant* | <input type="checkbox"/> Change* | <input type="checkbox"/> Renewal* |

1. Registered name of applicant:

2. Trading name (if different):

3. Addresses requiring approval:

4. Tel. Fax..... E-mail.....

5. Scope of approval relevant to this application: see page 2 for possibilities in the case of a ANO Part-M Subpart F/ ANO Part-145 approval:

6. Position and name of the (proposed*) Accountable Manager:

7. Signature of the (proposed*) Accountable Manager:

8. Place:

9. Date:

Note (1): A note giving the address(es) to which the CAAB Form(s) should be sent.**Note (2):** An optional note to give information on any fees payable.

* delete as applicable.

CAAB Form 2

SCOPE OF PART 145 APPROVAL AVAILABLE

CLASS	RATING	LIMITATION	BASE	LINE
AIRCRAFT	A1 Aeroplanes above 5700 kg	Quote aeroplane/airship type	YES/NO	YES/NO
	A2 Aeroplanes of 5700 kg and below	Quote aeroplane/airship manufacturer or group or	YES/NO	YES/NO
	A3 Helicopters	Quote helicopter manufacturer or group or type	YES/NO	YES/NO
	A4 Aircraft other than A1, A2 and A3	Quote aircraft type or group	YES/NO	YES/NO
ENGINES	B1 Turbine	Quote engine type		
	B2 Piston	Quote engine manufacturer or group or type		
	B3 APU	Quote engine manufacturer or type		
COMPONENTS OTHER THAN COMPLETE ENGINES OR APUs	C1 Air Cond & Press	Quote aircraft type or aircraft manufacturer or component manufacturer or the particular component and or cross refer to a capability list in the exposition.		
	C2 Auto Flight			
	C3 Comms and Nav			
	C4 Doors – Hatches			
	C5 Electrical Power & Lights			
	C6 Equipment			
	C7 Engine – APU			
	C8 Flight Controls			
	C9 Fuel			
	C10 Helicopter –Rotors			
	C11 Helicopter –Trans			
	C12 Hydraulics Power			
	C13 Indicating-recording system			
	C14 Landing Gear			
	C15 Oxygen			
	C16 Propellers			
	C17 Pneumatic & Vacuum			
	C18 Protection ice/rain/fire			
	C19 Windows			
	C20 Structural			
	C21 Water ballast Structural			
	C22 Propulsion Augmenttion			
SPECIALISED SERVICES	D1 Non Destructive Testing	Quote particular NDT method.		

With reference to the above scope of approval and item 6 on page 1, please complete the following example style, but relevant to your organisation.

A1	Base & Line Boeing 737-200	B2	Lycoming Piston
A2	Base Piper PA34	B3	Garrett GTCP85
A2	Base & Line Cessna Piston Twins	C2	SFENA
A3	Base & Line Bell 206/212	C4	Boeing 747
B1	CFM 56	D1	Eddy Current

There may be a number of types/manufacturers, etc listed against each rating.

CAAB Form 2

*Appendix IV to AMC 145.A.30(e):
Fuel Tank Safety Training*

This appendix includes general instructions for providing training on Fuel Tank Safety issues.

A) Effectivity:

- Large aeroplanes as defined in Part 145.A.1(e)

B) Affected organisations:

- Part-145 approved maintenance organisations involved in the maintenance of aeroplanes specified in paragraph A and fuel system components installed on such aeroplanes when the maintenance data are affected by CDCCL.
- Competent authorities responsible for the oversight of the Part-145 approved organisations specified in this paragraph B.

C) Persons from affected organisations who should receive training:

Phase 1 only:

- The group of persons representing the maintenance management structure of the organisation, the quality manager and the staff required to quality monitor the organisation.
- Personnel of the Competent Authorities responsible as per 145.B.30 for the oversight of Part-145 approved maintenance organizations specified in paragraph B.

Phase 1 + Phase 2 + Continuation training:

- Personnel of the Part-145 approved maintenance organization required to plan, perform, supervise, inspect and certify the maintenance of aircraft and fuel system components specified in paragraph A.

D) General requirements of the training courses

Phase 1 – Awareness:

The training should be carried out before the person starts to work without supervision but not later than 6 months after joining the organisation. The persons who have already attended the Level 1 Familiarisation course in compliance with the initial issue of Part 145 Appendix IV is already in compliance with Phase 1.

Type: Should be an awareness course with the principle elements of the subject. It may take the form of a training bulletin, or other self-study or informative session. Signature of the reader is required to ensure that the person has passed the training.

Level: It should be a course at the level of familiarisation with the principle elements of the subject.

Objectives:

The trainee should, after the completion of the training:

1. Be familiar with the basic elements of the fuel tank safety issues.
2. Be able to give a simple description of the historical background and the elements requiring a safety consideration, using common words and showing examples of non-conformities.
3. Be able to use typical terms.

Content:

The course should include:

- a short background showing examples of FTS accidents or incidents,
- the description of concept of fuel tank safety and CDCCL,
- some examples of manufacturers documents showing CDCCL items,
- typical examples of FTS defects,
- some examples of TC holders repair data,
- some examples of maintenance instructions for inspection.

Phase 2 - Detailed training

A flexible period may be allowed by the CAAB to allow organisations to set the necessary courses and impart the training to the personnel, taking into account the organisation's training schemes/means/practices. This flexible period should not extend beyond a date to be determined by the CAAB.

The persons who have already attended the Level 2 Detailed training course in compliance with the initial issue of Part 145 Appendix IV either from a Part-145 maintenance organisation or from a Part-147 training organisation are already in compliance with Phase 2 with the exception of continuation training.

Staff should have received Phase 2 training within 12 months of joining the organisation.

Type: Should be a more in-depth internal or external course. It should not take the form of a training bulletin, or other self-study. An examination should be required at the end, which should be in the form of a multi choice question, and the pass mark of the examination should be 75%.

Level: It should be a detailed course on the theoretical and practical elements of the subject.

The training may be made either:

- in appropriate facilities containing examples of components, systems and parts affected by Fuel Tank Safety (FTS) issues. The use of films, pictures and practical examples on FTS is recommended; or
- by attending a distance course (e-learning or computer based training) including a film when such film meets the intent of the objectives and content here below. An e-learning or computer based training should meet the following criteria:
 - A continuous evaluation process should ensure the effectiveness of the training and its relevance;
 - Some questions at intermediate steps of the training should be proposed to ensure that the trainee is authorized to move to the next step;
 - The content and results of examinations should be recorded;
 - Access to an instructor in person or at distance should be possible in case support is needed.

A duration of 8 hours for phase 2 is an acceptable compliance.

When the course is provided in a classroom, the instructor should be very familiar with the data in Objectives and Guidelines. To be familiar, an instructor should have attended himself a similar course in a classroom and made additionally some lecture of related subjects.

Objectives:

The attendant should, after the completion of the training:

- have knowledge of the history of events related to fuel tank safety issues and the theoretical and practical elements of the subject, have an overview of the FAA regulations known as SFAR (Special FAR) 88 of the FAA and of JAA Temporary Guidance Leaflet TGL 47, be able to give a detailed description of the concept of fuel tank system ALI (including Critical Design Configuration Control Limitations CDCCL, and using theoretical fundamentals and specific examples;
- have the capacity to combine and apply the separate elements of knowledge in a logical and comprehensive manner;
- have knowledge on how the above items affect the aircraft;
- be able to identify the components or parts or the aircraft subject to FTS from the manufacturer's documentation,
- be able to plan the action or apply a Service Bulletin and an Airworthiness Directive.

Content:

Following the guidelines described in paragraph E.

Continuation training:

The organisation should ensure that the continuation training is required in each two years period. The syllabus of the training programme referred to in 3.4 of the Maintenance Organisation Exposition (MOE) should include the additional syllabus for this continuation training.

The continuation training may be combined with the phase 2 training in a classroom or at distance.

The continuing training should be updated when new instruction are issued which are related to the material, tools, documentation and manufacturer's or CAAB's directives.

E) Guidelines for preparing the content of Phase 2 courses.

The following guidelines should be taken into consideration when the phase 2 training programme are being established:

- (a) understanding of the background and the concept of fuel tank safety,
- (b) how the mechanics can recognise, interpret and handle the improvements in the instruction for continuing airworthiness that have been made or are being made regarding the fuel tank system maintenance,
- (c) awareness of any hazards especially when working on the fuel system, and when the Flammability Reduction System using nitrogen is installed.

Paragraphs a) b) and c) above should be introduced in the training programme addressing the following issues:

- (i) The theoretical background behind the risk of fuel tank safety: the explosions of mixtures of fuel and air, the behaviour of those mixtures in an aviation environment, the effects of temperature and pressure, energy needed for ignition etc, the ‘fire triangle’, - Explain 2 concepts to prevent explosions:
 - (1) ignition source prevention, and
 - (2) flammability reduction,
- (ii) The major accidents related to fuel tank systems, the accident investigations and their conclusions,
- (iii) SFAR 88 of the FAA and JAA Interim Policy INT POL 25/12: ignition prevention program initiatives and goals, to identify unsafe conditions and to correct them, to systematically improve fuel tank maintenance,
- (iv) Explain the briefly concepts that are being used: the results of SFAR 88 of the FAA and JAA INT/POL 25/12: modifications, airworthiness limitations items and CDCCL,
- (v) Where relevant information can be found and how to use and interpret this information in the instructions for continuing airworthiness (aircraft maintenance manuals, component maintenance manuals, Service Bulletins...),

- (vi) Fuel Tank Safety during maintenance: fuel tank entry and exit procedures, clean working environment, what is meant by configuration control, wire separation, bonding of components etc,
- (vii) Flammability reduction systems when installed: reason for their presence, their effects, the hazards of an FRS using nitrogen for maintenance, safety precautions in maintenance/working with an FRS,
- (viii) Recording maintenance actions, recording measures and results of inspections.

The training should include a representative number of examples of defects and the associated repairs as required by the TC / STC holders' maintenance data.

F) Approval of training

For Part-145 approved organisations, the approval of the initial and continuation training programme and the content of the examination can be achieved by the change to the MOE. The necessary changes to the MOE to meet the content of this decision should be made and implemented at the time requested by the CAAB.

REPEAL AND SAVINGS

This ANO Part-145 will repeal and savings as per the followings:

- (a) As soon as may be after the commencement of this ANO Part-145, Issue-3, the ANO (AW) B.1, ANO (AW) B.2, ANO (AW) B.3A, ANO(AW) B.7, ANO (AW) B.10, ANO(AW) B.20, ANO(AW) C.1, ANO(AW) C.2, ANO(AW) C.4, ANO(AW) C.5, ANO(AW) C.6 and ANO(AW) C.7 shall stand repealed.
- (b) Despite such repeal under paragraph (a),
1. any act done, measures taken, works done, any order, circular, or notice issued, certificate, license or permit given or any agreement entered into or document signed under the said ANO (AW) B.1, ANO (AW) B.2, ANO (AW) B.3A, ANO(AW) B.7, ANO (AW) B.10, ANO(AW) B.20, ANO(AW) C.1, ANO(AW) C.2, ANO(AW) C.4, ANO(AW) C.5, ANO(AW) C.6 and ANO(AW) C.7 shall be deemed to have done, taken, entered, issued, given, made or signed under this ANO;
 2. any proceeding, going on or pending, shall, in so far as possible, be disposed of under this ANO; and
- (c) any suit and other legal proceedings instituted before any court shall, if pending, be disposed of in such way as if the said ANO (AW) B.1, ANO (AW) B.2, ANO (AW) B.3A, ANO(AW) B.7, ANO (AW) B.10, ANO(AW) B.20, ANO(AW) C.1, ANO(AW) C.2, ANO(AW) C.4, ANO(AW) C.5, ANO(AW) C.6 and ANO(AW) C.7 had not been repealed.